

ARENA



For the most up-to-date product information, scan the QR code.

12" x 48" Paver in Ash



24" x 24" Chalk in Anti-Slip



12" x 12" | 12" x 24" | 24" x 24" | 24" x 36" Heirloom Blue in Anti-Slip



24" x 24" Dark Grey in Anti-Slip



24" x 24" Paver in Light Grey



24" x 24" Paver in Manhattan Grey

SPECIAL ORDER ITEMS:

20mm Paver - Rectified Edge		
SIZE	FINISH	COLORS
12" x 12"	Anti-Slip	Heirloom Blue Legacy White Antique Cream
12" x 24"	Anti-Slip	
12" x 48"	Anti-Slip	Chalk Greige Ash MW White Honey Grey QT White Grey Extra White
24" x 24"	Anti-Slip	Chalk Greige Ash AR White Clay Steel Black Multicolor Dark Grey Light Grey Manhattan Grey Miami White Moon White Slate Millstone Pewter Alabaster Heirloom Blue Legacy White Antique Cream QT White Grey Extra White Intaglio Cool Intaglio Kaolin Intaglio Warm Cobblestone Bold Navona Roman Silver Titanium UT Ash Cool Sage Warm UT White
24" x 36"	Anti-Slip	Heirloom Blue Legacy White Antique Cream
24" x 48"	Anti-Slip	Slate Chalk Greige Ash Millstone Pewter Alabaster AR White Clay Steel Black Heirloom Blue Legacy White Antique Cream QT White Grey Extra White Bold Navona Roman Silver Titanium

All Sizes are Nominal.



24" x 48" Paver in Millstone

COLORS:



Colors shown may vary from actual product. Final selection should be made from actual product samples. Products and availability are subject to change, please refer to our website for the most up to date selection.



24" x 48" Paver in Legacy White

Features	Test Method	Value
Dimensions	ASTM C499	Compliant
Surface Quality		Min. 95% of tiles free of visible defects
Warpage	ASTM C485	Compliant
Wedging	ASTM C502	Compliant
Water Absorption	ASTM C373	≤ 0.5%
Breaking Strength	ASTM C648	≥ 2500 lbf
Thermal Shock Resistance	ASTM C484	Resistant
Crazing Resistance	ASTM C424	Resistant
Chemical Resistance (Domestic)	ASTM C650	UA
Chemical Resistance (Low Concentration)		LA
Chemical Resistance (High Concentration)		HA
Fire Resistance	-	A1/A1 _{FL}
Slip Resistance (Wet)	ANSI A326.3	DCOF 0.60
LEED	-	Yes
Recycled Content	-	≥ 25%
VOC Emissions	-	Zero VOC
Environmental Product Declaration	-	Yes
Health Product Declaration	-	Yes
Greenguard	-	Greenguard Gold
Green Squared	-	Yes
Declare	-	Red List Free








This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

- Product Info:**
- Porcelain Paver
 - Anti-Slip Finish
 - 20mm Thickness
 - Rectified Edge
 - V2 - Slight Shading
 - V3 - Moderate Variation
 - Frost Resistant



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.



www.genrose.com