

ATRIUM

 **GENROSE**





12"x24" Field Tile in Blu



AVAILABLE IN:

9mm Field Tile

Rectified Edge

12"x12" Matte Finish

9mm Field Tile

Pressed Edge

12"x24" Matte Finish

Mosaics

2"x2"

Mosaic Matte Finish

3"x4"


Hexagon Mosaic Matte Finish

Trim Piece

3"x24"

Bullnose Matte Finish






- All sizes are NOMINAL



MADE TO ORDER FIELD TILES AND MOSAICS:

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		2" 4"		1 ³ / ₈ "x3" 2"x4"
		BRICKS		DIAMONDS	
			1"x2" 1"x3" 1 ³ / ₈ "x3" 2"x4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
 Half Hexagon	6.7" Base		2"x12"		1"x2" 2"x4" 5 ⁵ / ₈ "x4"
 Diamond	4"	OCTAGONS		HEXAGONS	
 Hexagon	6"		2" w/ 0.6" Squares		1 ¹ / ₈ " 2"
 Chevron	2"x12" 6"x24"	SQUARES		RECTANGLES	
	4"x2 ¹ / ₂ " w/ 5 ⁵ / ₈ " Dot		1"x1" 1 ³ / ₈ "x1 ³ / ₈ " 2"x2" 3"x3"		1"x2" 1"x4"

*Other sizes available upon request



Avorio



Blu




Nero

Colors shown may vary from actual product. Final selection should be made from actual product samples.


2"X2" MOSAIC



Luce



Bianco



Sabbia


3"X4" HEXAGON MOSAIC



Luce



Bianco



Sabbia



3"x4" Hexagon Mosaic in Nero
12"x24" Field Tile in Nero

Features	Test Method	Value
Length and Width	ISO 10545-2	± 0.5%
Thickness		± 5%
Wedging		± 0.6%
Warpage		± 0.5%
Water Absorption	ISO 10545-3	≤ 0.5%
Bending Strength	ISO 10545-4	R ≥ 35 N/mm ²
Deep Abrasion Resistance	ISO 10545-6	123 mm ³
Coefficient of Linear Thermal Expansion	ISO 10545-8	9x10 ⁻⁵ xC ⁻¹
Thermal Shock Resistance	ISO 10545-9	Resistant
Crazing Resistance	ISO 10545-11	Resistant
Frost Resistance	ISO 10545-12	Resistant
Chemical Resistance	ISO 10545-13	Min. B
Stain Resistance	ISO 10545-14	Min. Class 3
Slip Resistance	DCOF (Wet)	≥ 0.5
	DIN 51130 R	R10

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Matte Finish
- 9mm Thickness
- Rectified | Pressed Edge
- V2 - Slight Shading Variation
- Frost Resistance = Yes


www.genrose.com



www.genrose.com