

BRIXTON

 **GENROSE**



For the most up-to-date product information, scan the QR code.

24" x 36" Paver in Everywhere Greige



24" x 36" Paver in Wander White



24" x 36" Paver in Leisure Grey



24" x 36 Paver in Wander White

SPECIAL ORDER ITEMS:

9mm Field Tile - Rectified Edge			
SIZE	FINISH		COLORS
12" x 24"	Matte		Wander White Everywhere Greige Anywhere Beige Leisure Gray
24" x 24"			
9mm Field Mosaics - Rectified Edge			
SHEET SIZE	TYPE	FINISH	COLORS
12" x 12"	2" x 2"	Matte	Wander White Everywhere Greige Anywhere Beige Leisure Gray
12" x 24"	Random Stack		
9mm Trim Pieces - Rectified Edge			
SIZE	FINISH		COLORS
24" x 36"	Matte		Wander White Everywhere Greige Anywhere Beige Leisure Gray
20mm Pavers - Rectified Edge			
SIZE	FINISH		COLORS
24" x 36"	Matte		Wander White Everywhere Greige Anywhere Beige Leisure Gray



24" x 36" Paver in Everywhere Greige

COLORS:



Leisure Gray



Anywhere Beige



Everywhere Greige









Wander White

Colors shown may vary from actual product. Final selection should be made from actual product samples. Products and availability are subject to change, please refer to our website for the most up to date selection.



24" x 36" Paver in Anywhere Beige

Features	Test Method	Value	
Dimensions	ASTM C499	Compliant	
Surface Quality		Min. 95% of tiles free of visible defects	
Warpage	ASTM C485	Compliant	
Wedging	ASTM C502	Compliant	
Water Absorption	ASTM C373	≤ 0.5%	
Breaking Strength	ASTM C648	9mm	20mm
		≥ 450 lbf	≥ 2800 lbf
Chemical Resistance (Domestic)	ASTM C650	Conforms	
Recycled Content	-	40%	
Slip Resistance (DCOF)	ANSI A326.3	> 0.42	
LEED	-	Yes	
Environmental Product Declaration	-	Yes	
Greenguard Gold		Yes	
Green Squared		Yes	
Declare	-	Red List Free	
VOC Emissions	-	Zero VOC	







 This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Porcelain Tile
- Matte Finish
- 9mm | 20mm Thicknesses
- Rectified Edge
- V3 - Moderate Variation
- Frost Resistant





www.genrose.com