

# CATALAN



For the most up-to-date product information, scan the QR code.

Hexagon Deco Mosaic in Woodchunk





8" x 48" Floor/Wall Tile in Woodchunk





8" x 48" Floor/Wall Tile in Champagne



Herringbone Mosaic in Dune  
(Dune | Nutmeg | Champagne)





Leaf Mosaic in Dune



AVAILABLE STOCKED ITEMS:

9mm Floor/Wall Tiles - Rectified Edge				
SIZE		FINISH		COLORS
8" x 48"		Natural		Dune   Champagne   Nutmeg   Woodchunk
9mm Mosaics - Rectified Edge				
SHEET SIZE	MOSAIC SIZE	Mosaic Type	FINISH	COLORS
12" x 14"	6.5" x 7.5"	Hexagon Deco	Natural	Dune   Champagne   Nutmeg   Woodchunk
11" x 11"	1.75" 3.75"	Herringbone	Natural	Dune (Nutmeg   Champagne) Woodchunk (Nutmeg   Champagne)
9" x 13"	2" x 5.5"	Leaf	Natural	Dune   Champagne   Nutmeg   Woodchunk

All Sizes are Nominal.

COLORS:



Dune



Champagne



Nutmeg



Woodchunk

V3 

Colors shown may vary from actual product. Final selection should be made from actual product samples.  
Products and availability are subject to change, please refer to our website for the most up to date selection.

HEXAGON DECO MOSAIC:



Dune



Champagne



Nutmeg



Woodchunk

LEAF MOSAIC:



Dune



Champagne



Nutmeg



Woodchunk

HERRINGBONE MOSAIC:



Dune  
(Nutmeg | Champagne)



Woodchunk  
(Nutmeg | Champagne)



8" x 48" Floor/Wall Tile in Champagne





8" x 48" Floor/Wall Tile in Champagne

Features	Test Method	Value
Dimensions	ISO 10545 - 2	Compliant
Surface Quality		Min. 95% of tiles free of visible defects
Water Absorption	ISO 10545 - 3	Average 0.08%
Modulus of Rupture / Bending Strength	ISO 10545 - 4	Average 50 N/mm <sup>2</sup>
Breaking Strength		Average 2200N
Deep Abrasion Resistance	ISO 10545 - 6	Average 140/mm <sup>3</sup>
Thermal Shock Resistance	ISO 10545 - 9	Resistant
Crazing Resistance	ISO 10545 - 11	Resistant
Chemical Resistance (Domestic)	ISO 10545 - 13	UA
Chemical Resistance (Low Concentration)		ULA
Slip Resistance	ANSI A326.3	DCOF 0.70
LEED	-	Yes
Recycled Content	-	24%
VOC Emissions	-	Zero VOC
Environmental Product Declaration	-	Facility-Specific
Health Product Declaration		Available
Greenguard	-	Greenguard Gold
<div></div> <div>This product will contricute to USGBC registered LEED projects. It will also contricute to the ANSI approved NAHB Green Building Standard ICC 700.</div>		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Disclaimer:** DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Glazed Porcelain Tile
- Natural Finish
- 9mm Thickness
- Rectified Edge
- V3 - Moderate Variation
- Frost Resistance - Yes





