

CHATHAM



GENROSE



For the most up-to-date product information, scan the QR code.

8" x 48" Field Tile in Rovere



12" x 48" | 8" x 48" Field Tile in Acero
24" x 48" Field Deco in Acero



12" x 48" | 8" x 48" Field Tile in Rovere

AVAILABLE STOCKED ITEMS:

10mm Field Tile - Rectified Edge		
SIZE	FINISH	COLORS
8" x 48"	Matte	Rovere Acero Noce
10mm Field Deco - Rectified Edge		
SIZE	FINISH	COLORS
24" x 48"	Matte	Rovere Acero Noce

AVAILABLE SPECIAL ORDER ITEMS:

10mm Field Tile - Rectified Edge		
SIZE	FINISH	COLORS
12" x 48"	Matte	Rovere Acero Noce

All Sizes are Nominal.

8" X 48" FIELD TILE:



Rovere Acero Noce

12" X 48" FIELD TILE:



Rovere Acero Noce

Colors shown may vary from actual product. Final selection should be made from actual product samples. Products and availability are subject to change, please refer to our website for the most up to date selection.



12" x 48" | 8" x 48" Field Tile in Noce
24" x 48" Field Deco in Noce

24” X 48” FIELD DECO:



Rovere







Acero



Noce



12” x 48” | 8” x 48” Field Tile in Noce

Features	Test Method	Value
Dimensions	ISO 10545 - 2	Compliant
Surface Quality		Min. 95% of tiles free of visible defects
Water Absorption	ISO 10545 - 3	Eb < 0.5%
Modulus of Rupture / Bending Strength	ISO 10545 - 4	≥ 35 N/mm²
Breaking Strength		≥ 1300 N
Deep Abrasion Resistance	ISO 10545 - 6	< 150 MM³
Coefficient of Linear Thermal Expansion	ISO 10545 - 8	< 9MK-1
Thermal Shock Resistance	ISO 10545 - 9	Resistant
Crazing Resistance	ISO 10545 - 11	Resistant
Chemical Resistance (Domestic)	ISO 10545 - 13	UA
Chemical Resistance (Low Concentration)		ULA-ULB
Chemical Resistance (High Concentration)		UHA-UHB
Fire Resistance	-	A1/A1 _{FL}
Slip Resistance	ANSI A326.3	DCOF 0.52
LEED	-	Yes
Recycled Content	-	≥ 20%
VOC Emissions	-	Zero VOC
Declare	-	Red List Free
Environmental Product Declaration	-	Industry Wide
Health Product Declaration	-	Available
<div><div></div><div>This product will contricute to USGBC registered LEED projects. It will also contricute to the ANSI approved NAHB Green Building Standard ICC 700.</div></div>		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8” wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16” wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

- Product Info:**
- Color Body Porcelain Tile
 - Matte Finish
 - 10mm Thickness
 - Rectified Edge
 - V3 - Moderate Variation
 - Frost Resistance = Yes



