

CINDER



GENROSE



For the most up-to-date product information, scan the QR code.

4" x 8" Field Tile in Back Bay
6" x 7" Hexagon Field Tile in Back Bay



4"x 8" Field Tile in North End
6" x 7" Hexagon Field Tile in North End



4"x 8" Field Tile in Southie
6" x 7" Hexagon Field Tile in Southie



4"x 8" Field Tile in North End



4"x 8" Field Tile in Revere



4"x 8" Field Tile in Revere
6" x 7" Hexagon Field Tile in Seaport



4"x 8" Field Tile in Seaport
6" x 7" Hexagon Field Tile in Seaport

AVAILABLE STOCKED ITEMS:

10mm Field Tiles - Pressed Edge		
SIZE	FINISH	COLORS
4"x 8"	Natural	Seaport Southie Back Bay North End Revere
6"x 7" Hexagon	Natural	Seaport Southie Back Bay North End Revere

All Sizes are Nominal.



4"x 8" Field Tile in North End

COLORS:



Seaport



Southie



North End



Revere






Back Bay





4"x 8" Field Tile in Back Bay
6" x 7" Hexagon Field Tile in Back Bay

Features	Test Method	Value
Length and Width	ISO 10545 - 2	± 0.5% ± 2mm
Thickness		± 5% ± 0.5mm
Straightness of Sides		± 0.5% ± 2mm
Rectangularity		± 0.5% ± 2mm
Surface Flatness		± 0.5% ± 2mm
Surface Quality		Min. 95% of tiles free of visible defects
Water Absorption	ISO 10545 - 3	≤ 0.3%
Modulus of Rupture/ Bending Strength	ISO 10545 - 4	R ≥ 35 N/mm ²
Breaking Strength		S ≥ 1300 N
Thermal Shock Resistance	ISO 10545 - 9	Resistant
Crazing Resistance	ISO 10545 - 11	Resistant
Chemical Resistance (Domestic)	ISO 10545 - 13	A
Chemical Resistance (Low Resistance)		LA
Chemical Resistance (High Resistance)		HA
Slip Resistance	ANSI A326.3	DCOF 0.72
LEED	-	Yes
Recycled Material	-	20% Pre-Consumer
Environmental Product Declaration	-	Yes
VOC Emissions	-	Zero VOC



This product will contricute to USGBC registered LEED projects.
It will also contricute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

- Product Info:**
- Glazed Porcelain Tile
 - Natural Finish
 - 10mm Thickness
 - Pressed Edge
 - PEI Rating = 4
 - Frost Resistance = Yes
 - V4 - **EXTREME** Variation



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.



www.genrose.com