

CYPRUS



For the most up-to-date product information, scan the QR code.

2.5" x 10" Floor/ Wall Tile in Green



2.5" x 10" Floor/Wall Tile in White



2.5" x 10" Floor/Wall Tile in Blu



2.5" x 10" Floor/Wall Tile in Cotto



2.5" x 10" Floor/Wall Tile in Ocre



2.5" x 10" Floor/Wall Tile in Light Grey

AVAILABLE STOCKED ITEMS:


9.5mm Field Tiles - Pressed Edge			
SIZE	FINISH		COLORS
2.5" x 10"	Polished		White Light Grey Denim Blu Sea Water Green Ocra Cotto
9.5mm Trim Pieces - Pressed Edge			
SIZE	TYPE	FINISH	COLORS
10"	Finishing Strip	Polished	White Light Grey Denim Blu Sea Water Green Ocra Cotto

All Sizes are Nominal.



2.5" x 10" Floor/Wall Tile in Denim

COLORS:



White

v1



Light Grey



Denim



Sea Water



Ocra



Blu



Green




Cotto

Colors shown may vary from actual product. Final selection should be made from actual product samples. Products and availability are subject to change, please refer to our website for the most up to date selection.






2.5" x 10" Field Tile in Sea Water



GENROSE

CYPRUS
Glazed Porcelain Tile

Features	Test Method	Value
Length and Width	ISO 10545-2	Compliant
Thickness		Compliant
Straightness of Sides		Compliant
Rectangularity		Compliant
Surface Flatness		Compliant
Water Absorption	ISO 10545-3	< 0.2%
Modulus of Rupture/ Bending Strength	ISO 10545-4	> 45 N/mm ²
Breaking Strength		Compliant
Coefficient of Linear Thermal Expansion	ISO 10545-8	$\alpha \leq 7.1 \times 10^{-6} \text{ }^{\circ}\text{C}^{-1}$
Thermal Shock Resistance	ISO 10545-9	Resistant
Chemical Resistance (Domestic)	ISO 10545-13	A
Chemical Resistance (Low Concentration)		LA
Chemical Resistance (High Concentration)		HA
Fire Resistance	-	A1/A1 _{FL}
Slip Resistance	ANSI A137.1	DCOF Does Not Pass
LEED	-	Yes
Recycled Content	-	52%
VOC Emissions	-	Zero VOC
Material Health Certification	-	Red List Free, Certificate Available
Environmental Product Declaration	-	Yes



This product will contribute to USGBC registered LEED projects.
It will also contricute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

- Product Info:**
 - Glazed Porcelain Tile
 - Polished Finish
 - 9.5mm Thickness
 - Pressed Edge
 - Frost Resistance = Yes
- PEI Rating by Color:
 - Light Grey | White - 5
 - Blu | Denim | Green | Ocre | Sea Water - 4
 - Cotto - 3
 - V1 - Uniformed Appearance - *White*
 - V3 - Moderate Shading Variation - *All Other Colors*



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.



www.genrose.com