

**ECOTOUCH**



For the most up-to-date product information, scan the QR code.

24" x 24" Paver in Natural



24" x 24" Paver in Alabaster



24" x 24" Paver in Feldspar

## AVAILABLE SPECIAL ORDER ITEMS:

20mm Pavers - Pressed Edge		
SIZE	FINISH	COLORS
24" x 24"	Natural	Alabaster   Snow   Silver   Feldspar   Quartz   White Range   Grey Range   Greige Range

All Sizes are Nominal.



24" x 24" Paver in Cinder

## COLORS:




Alabaster

V2



Snow

V2



Feldspar

V3



Silver

V2



Quartz






V3

Colors shown may vary from actual product. Final selection should be made from actual product samples.



24" x 24" Paver in Alabaster

Features	Test Method	Value
Dimensions	ASTM C499	Compliant
Surface Quality		Min. 95% of tiles free of visible defects
Warpage	ASTM C485	Compliant
Wedging	ASTM C502	Compliant
Water Absorption	ASTM C373	≤ 0.5%
Breaking Strength	ASTM C648	≥ 2800 lbf.
Thermal Shock Resistance	ASTM C484	Resistant
Crazing Resistance	ASTM C424	Resistant
Chemical Resistance (Domestic)	ASTM C650	UA
Chemical Resistance (Low Concentration)		UA
Chemical Resistance (High Concentration)		UA
Slip Resistance	ANSI A326.3	DCOF 0.65
LEED	-	Yes
VOC Emissions	-	Zero VOC
Recycled Content		40%
Environmental Product Declaration		Yes
Health Product Declaration		Yes
Declare	-	Red List Free
Greenguard Gold	-	Yes
Green Squared Certified	-	Yes






 This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Disclaimer:** DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

**Product Info:**

- Color Body Porcelain Tile
- Natural Finish
- 20mm Thickness
- V2 - Slight Shading Variation (Alabaster | Snow | Silver)
- V3 - Moderate Variation (Ash | Feldspar | Cinder | Quartz)
- Rectified Edge
- Frost Resistant



[www.genrose.com](http://www.genrose.com)

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.



[www.genrose.com](http://www.genrose.com)