EMILIA









48"x48" Floor/Wall Tile in Calacatta

AVAILABLE IN:

Floor/Wall Tile

Rectified Edge

24" x24" 9.5mm Matte | Polished Finish 24"x48" 9.5mm Matte | Polished Finish 48"x48" 9mm Polished Finish

Mosaics

1″x1″ Mosaic Matte Finish

- All sizes are NOMINAL



MADE TO ORDER FIELD TILES AND MOSAICS:

Minimum quantity required. Contact your sales representative for more information.

This represents a small portion of the mosaic patterns we offer. We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE		
	Any 24" field tile can be cut down to		2" 4"		1³/8″x3″ 2″x4″	
	a smaller size in any length and width	BRICKS		DIAMONDS		
	combination with a 1" minimum.		1"x2" 1"x3" 1 ³ / ₈ "x3" 2"x4"		2"	
FIELD SHAPES*		CHEVRONS		HERRINGBONE		
Half Hexagon	6.7" Base		2"x12"		1"x2" 2"x4"	
Diamond	4"				⁵ / ₈ "×4"	
			OCTAGONS		HEXAGONS	
A Hexagon	6"		0.11			
Chevron	2"×12" 6"×24"		2" w/ 0.6" Squares		1 ¹ / ₈ " 2"	
TRAPEZO	DID W/ DOT SQUARES RECTANGLES		NGLES			
	4"x2 ¹ / ₂ " w/ ⁵ / ₈ " Dot		1"x1" 2"x2" 1 ³ / ₈ "x1 ³ / ₈ " 3"x3"		1"x2" 1"x4"	

Calacatta

*Other sizes available upon request

Arabescato





1"X1" MOSAIC





Calacatta

Arabescato





Features	Test Method	Value	
Length and Width		±0.6% (±2.00 MM)	
Thickness		±5% (±0.5 MM)	
Warpages of Edges	ISO 10545-2	±0.5% (±1.5 MM)	
Wedging		±0.5% (±2.00 MM)	
Flatness		±0.5% (±2.00 MM)	
Water Absorption	ISO 10545-3	≤ 0.5	
Bending Strength	ISO 10545 4	$R \ge 35N/MM^2$	
Breaking Strength	ISO 10545-4	S > 1300 N	
Linear Thermal Expansion Between 20° and 100°	ISO 10545-8	≈ 7X10 ⁻⁶ C ⁻¹	
Thermal Shock Resistance	ISO 10545-9	Resistant	
Frost Resistance	ISO 10545-12	Resistant	
Chemical Resistance	ISO 10545-13	Resistant	
Color Resistant To Light	DIN 51094	No Alteration	
Stain Resistance	ISO 10545.14	≥ Class 3	
DCOF (WET)	ANSI 137.1-2012	Matte: > 0.42	
Recycled Content	-	≥ 10%	



This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700. Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Matte | Polished Finishes
- 9.5mm | 9mm Thickness
- Rectified Edge
- V2 Slight Shading Variation
- Frost Resistance = Yes



www.genrose.com



www.genrose.com