

**FINESSE**

 **GENROSE**



# AVAILABLE IN:

## 8.2mm Field Tiles

Rectified Edge

12"x 24" *Matte* | *Polished Finish*


## Mosaic

2"x 2" Mosaic *Matte Finish*


## Trim

4"x 12" Bullnose *Polished Finish*

- All sizes are NOMINAL



**Ice White**



**2"x 2" Mosaic**



**Glacier Grey**



**2"x 2" Mosaic**

Colors shown may vary from actual product. Final selection should be made from actual product samples.

# MADE TO ORDER FIELD TILES AND MOSAICS:

Minimum quantity required. Contact your sales representative for more information.

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		2" 4"		1 3/8" x 3" 2" x 4"
		BRICKS		DIAMONDS	
			1" x 2" 1" x 3" 1 3/8" x 3" 2" x 4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
	Half Hexagon 6.7" Base		2" x 12"		1" x 2" 2" x 4" 5/8" x 4"
	Diamond 4"			HEXAGONS	
	Hexagon 6"				1 1/8" 2"
	Chevron 2" x 12" 6" x 24"	OCTAGONS			
			2" w/ 0.6" Squares		
TRAPEZOID W/ DOT		SQUARES		RECTANGLES	
	4" x 2 1/2" w/ 5/8" Dot		1" x 1"    2" x 2" 1 3/8" x 1 3/8"    3" x 3"		1" x 2" 1" x 4"

\*Other sizes available upon request

Features	Test Method	Value	
		Matte	Polished
<b>DCOF (Wet)</b>	ANSI A 137.1	≥ 0.42	n/a
<b>Breaking Strength</b>	ANSI C648	≥ 325 lbf	≥ 425 lbf
<b>Scratch Hardness (MOHS)</b>	-	7	4-5
<b>Water Absorption</b>	ASTM C373	< 0.5%	
<b>Chemical Resistance</b>	ASTM C650	Class A	
<b>Abrasion Resistance</b>	ASTM C1027	Class 4	—
<b>Thermal Shock Resistance</b>	ASTM C484	Resistant	
<b>Frost Resistance</b>	ASTM C1026	Resistant	

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.


**Product Info:**

- Glazed Porcelain Tile
- Matte | Polished Finishes
- 8.2mm Thickness
- Rectified Edge
- PEI Rating = 4 (matte only)
- V2- Slight Shading Variation
- Frost Resistance = Yes


[www.genrose.com](http://www.genrose.com)



[www.genrose.com](http://www.genrose.com)