



For the most up-to-date product information, scan the QR code.

6" x 6" Floor/Wall Deco in Siena Aqua



6" x 6" Floor/Wall Deco in Senda Aqua



6" x 6" Floor/Wall Deco in Serena Beige



6" x 6" Floor/Wall Deco in Serena Aqua



6" x 6" Floor/Wall Deco in Siena Beige



6" x 6" Floor/Wall Deco in Siena Aqua

## AVAILABLE STOCKED ITEMS:

7.4mm Floor/Wall Decorative Tiles - <i>Pressed Edge</i>					
SIZE	FINISH	DECO TYPE	COLORS		
6" x 6"	Matte	Siena	Siena Beige	Siena Aqua	Siena Denim
		Serena	Serena Beige	Serena Aqua	Serena Denim
		Senda	Senda Beige	Senda Aqua	Senda Denim

All Sizes are Nominal.



6" x 6" Floor/Wall Deco in Senda Beige

## COLORS:

### SIENA



Siena Beige



Siena Aqua



Siena Denim

### SERENA



Serena Beige



Serena Aqua



Serena Denim

### SENDA



Senda Beige



Senda Aqua



Senda Denim

Colors shown may vary from actual product. Final selection should be made from actual product samples. Products and availability are subject to change, please refer to our website for the most up to date selection.



6" x 6" Floor/Wall Deco in Serena Denim

Features	Test Method	Value
Length and Width	ISO 10545 - 2	Compliant
Thickness		Compliant
Straightness of Sides		Compliant
Rectangularity		Compliant
Surface Flatness		Compliant
Surface Quality		Min. 95% of tiles free of visible defects
Water Absorption	ISO 10545 - 3	< 0.5%
Modulus of Rupture / Bending Strength	ASTM C1505	≥ 35 N/mm <sup>2</sup>
Breaking Strength	ASTM C648	≥ 1300 N
Deep Abrasion Resistance	ISO 10545 - 6	≤ 9
Coefficient of Linear Thermal Expansion	ISO 10545 - 8	Compliant
Thermal Shock Resistance	ISO 10545 - 9	Resistant
Crazing Resistance	ISO 10545 - 11	Resistant
Chemical Resistance (Domestic)	ISO 10545 - 13	GA
Chemical Resistance (Low Concentration)		GLA
Chemical Resistance (High Concentration)		GHA
Fire Resistance	-	A1/A1 <sub>FL</sub>
Slip Resistance (Wet)	ANSI A326.3	0.52
LEED	-	Yes
VOC Emissions	-	Zero VOC



This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Disclaimer:** DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

**Product Info:**

- Glazed Porcelain Tile
- Matte Finish
- 7.4mm Thickness
- Pressed Edge
- V2 - Slight Variation
- Frost Resistance - Yes





[www.genrose.com](http://www.genrose.com)