

GLACIER



For the most up-to-date product information, scan the QR code.

12" x 24" Brick Mosaic in Platino
24" x 48" Floor/Wall Tile in Platino



12" x 24" | 24" x 24" Floor/Wall Tile in Oro



24" x 48" Floor/Wall Tile in Piombo



12" x 24" | 24" x 48" Floor/Wall Tile in Oro



12" x 24" | 24" x 48" Floor/Wall Tile in Magnesio
Brick Mosaic in Magnesio



24" x 48" Floor/Wall Tile in Platino



Path A + B Paver in Oro
Path C Paver in Oro

AVAILABLE STOCKED ITEMS:

9mm Floor/Wall Tiles - Rectified Edge			
SIZE	FINISH		COLORS
12" x 24"	Matte		Magnesio Oro Platino Piombo
9mm Floor/Wall Mosaics - Rectified Edge			
SHEET SIZE	TYPE	FINISH	COLORS
12" x 12"	2"x 2" Mosaic	Matte	Magnesio Oro Platino Piombo
12" x 24"	Brick Mosaic	Matte	

AVAILABLE SPECIAL ORDER ITEMS:

9mm Floor/Wall Field Tiles - Rectified Edge			
SIZE	FINISH		COLORS
24" x 24"	Matte		Magnesio Oro Platino Piombo
24" x 48"	Matte Anti-Slip		
20mm Outdoor Pavers + Special Shapes - Rectified Edge			
SIZE	FINISH		COLORS
24" x 24"	Anti-Slip		Magnesio Oro Platino Piombo
24" x 36"			
24" x 48"			
32" x 32"			
Path A + B			
Path C			
9mm Trim Pieces - Rectified Edge			
SIZE	TYPE	FINISH	COLORS
3" x 24"	Bullnose	Matte	Magnesio Oro Platino Piombo
12" x 24" *	Gradino	Matte	
13" x 24" *	Scalino	Matte	
13" x 48" *	Scalino	Matte	
13" x 13" *	Scalino Angolare	Matte	
13" x 48" *	Elemento L	Anti-Slip	

*Indicates Made to Order
All sizes are nominal.

COLORS:



Magnesio



Oro



Platino



Piombo

2”X2” MOSAIC:



Magnesio



Oro



Platino



Piombo

BRICK MOSAIC:



Magnesio



Oro



Platino



Piombo

OUTDOOR SPECIAL SHAPES:



Path A + B
in Magnesio



Path A + B
in Oro



Path A + B
in Platino



Path A + B
in Piombo



Path C
in Magnesio



Path C
in Oro



Path C
in Platino



Path C
in Piombo

INSTALLATION PATTERNS FOR OUTDOOR SPECIAL SHAPES:



Pattern with
Path A + B






Pattern with
Path A + B + C



Pattern with
Path C + C

MADE TO ORDER FIELD TILES AND MOSAICS:

This represents a small portion of the mosaic patterns we offer.
We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	16" x 32" 8" x 32" 8" x 24" 6" x 24" 6" x 12" 4" x 12"		2" 3" 4"		1 3⁄8" x 3" 2" x 4"
		BRICKS		DIAMONDS	
			1" x 2" 1" x 3" 1 3⁄8" x 3" 2" x 4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
 Half Hexagon	6.7" Base		2" x 12"		1" x 2" 2" x 4" 5⁄8" x 4"
 Diamond	4"	OCTAGONS		HEXAGONS	
 Hexagon	6"		2" w/ 0.6" Squares		1 1⁄8" 2"
 Chevron	2" x 12" 6" x 24"	SQUARES		RECTANGLES	
	4" x 2 1⁄2" w/ 5⁄8" Dot		1" x 1" 1 3⁄8" x 1 3⁄8" 2" x 2" 3" x 3"		1" x 2" 1" x 4"

*Other sizes available upon request



24" x 48" Field Tile in Oro



GENROSE

GLACIER

Color Body Porcelain Tile

Features	Test Method	Value		
Dimensions	ISO 10545 - 2	Compliant		
Surface Quality		Min. 95% of tiles free of visible defects		
Water Absorption	ISO 10545 - 3	≤ 0.1%		
Modulus of Rupture	ISO 10545 - 4	9mm	20mm	
		≥ 1500 N	≥ 10000 N	
Breaking Strength		≥ 40 N/mm²	≥ 45 N/mm²	
Deep Abrasion Resistance	ISO 10545 - 6	≤ 150 mm³		
Coefficient of Linear Thermal Expansion	ISO 10545 - 8	≤ 7 MK ⁻¹		
Thermal Shock Resistance	ISO 10545 - 9	Resistant		
Crazing Resistance	ISO 10545 - 11	Resistant		
Chemical Resistance (Domestic)	ISO 10545 - 13	A		
Chemical Resistance (Low Concentration)		LA		
Chemical Resistance (High Concentration)		HA		
Fire Resistance	-	A1/A1 _{FL}		
Slip Resistance (Wet)	ANSI A326.3	Matte	Anti-Slip	Pavers
		DCOF 0.67	DCOF 0.78	DCOF 0.74
LEED	-	Yes		
Recycled Material	-	10%		
Environmental Product Declaration	-	Product-Specific		
Health Product Declaration	-	Available		
Declare	-	Red List Free		
Greenguard	-	Greenguard Gold		
VOC Emissions	-	Zero VOC		



This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.



Declare.

This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Color Body Porcelain Tile
 - Matte | Anti-Slip Finishes
 - 9mm | 20mm Thicknesses
- Rectified Edge
 - V3 - Moderate Variation
 - Frost Resistant



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.



www.genrose.com