

**KENSINGTON**



For the most up-to-date product information, scan the QR code.

12" x 24" Floor/ Wall Tile in Historic Greige



24" x 36" Paver in Atlas Gray

## AVAILABLE STOCKED ITEMS:

9mm Floor/Wall Tiles - Rectified Edge			
SIZE	FINISH	COLORS	
12" x 24"	Matte	Antique White   Historic Greige   Atlas Gray	
9mm Floor/Wall Mosaic - Rectified Edge			
SIZE	TYPE	FINISH	COLORS
1.5" x 3"	Offset Basketweave	Matte	Antique White

## SPECIAL ORDER ITEMS:

9mm Floor/Wall Tiles - Rectified Edge			
SIZE	FINISH	COLORS	
24" x 24"	Matte	Antique White   Historic Greige   Atlas Gray	
20mm Pavers - Rectified Edge			
SIZE	FINISH	COLORS	
24" x 36"	Matte	Antique White   Historic Greige   Atlas Gray	
Trim Pieces - Rectified Edge			
SIZE	TYPE	FINISH	COLORS
12" x 24"	Step Tread w/Square	Matte	Antique White   Historic Greige   Atlas Gray
12" x 24"	Step Tread w/ Bullnose Edge		

All Sizes are Nominal.

## COLORS:



Antique White



Historic Greige



Atlas Gray

Colors shown may vary from actual product. Final selection should be made from actual product samples. Products and availability are subject to change, please refer to our website for the most up to date selection.

## OFFSET BASKETWEAVE MOSAIC:



Antique White



24" x 36" Paver in Historic Greige



**KENSINGTON**  
Color Body Porcelain Tile

Features	Test Method	Value	
Dimensions	ASTM C499	Compliant	
Surface Quality		Min. 95% of tiles free of visible defects	
Warpage	ASTM C485	Compliant	
Wedging	ASTM C485	Compliant	
Water Absorption	ASTM C373	≤ 0.5%	
Coefficient of Linear Thermal Expansion	ASTM C372	Compliant	
Breaking Strength	ASTM C648	<b>9mm</b>	<b>20mm</b>
		450 lbf	2800 lbf
Thermal Shock Resistance	ASTM C484	Resistant	
Slip Resistance (Wet)	ANSI A326.3	DCOF 0.70	
Recycled Content	-	40%	
LEED	-	Yes	
Greenguard Gold	-	Yes	
Green Squared	-	Yes	
VOC Emissions	-	Zero VOC	

This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Disclaimer:** DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

**Product Info:**

- Color Body Porcelain Tile
- Matte Finish
- 9mm | 20mm Thicknesses
- Rectified Edge
- V3 - Moderate Variation
- Frost Resistant



[www.genrose.com](http://www.genrose.com)

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.



[www.genrose.com](http://www.genrose.com)