

**LEGACY**



**GENROSE**







40"x70" 8mm Field Tile - Available in: Brushed/Shaped | Premium Polished Finish  
 30"x60" 10mm Field Tile - Available in: Matte | Polished Finish



40"x70" 8mm Field Tile in White  
 40"x70" 8mm Available in: Brushed/Shaped | Premium Polished Finish



AVAILABLE IN:

Field Tiles  
Rectified Edge

- 40"x102" 6mm MatteFinish
- 40"x70" 8mm Brushed/Shaped | Premium Polished Finish
- 40"x40" 8mm Brushed/Shaped | Premium Polished Finish
- 20"x40" 8mm Brushed/Shaped | Premium Polished Finish
- 30"x60" 10mm Matte | Polished Finish
- 24"x48" 10mm Matte | Polished Finish

- All sizes are NOMINAL



24"x48" 10mm Field Tile in White  
Available in: Matte | Polished Finish

COLOR



White

Colors shown may vary from actual product. Final selection should be made from actual product samples.





40"x70" 8mm Field Tile in White - Available in: Brushed/Shaped | Premium Polished Finish

Features	Test Method	Value	
		Brushed/Shaped   Polished	Matte
Surface Quality	ISO 10545-2	> 95%	
Curvature Flatness	ISO 10545-2	± 0.5 % / ± 2.0 mm	
Thickness	ISO 10545-2	± 5% / ± 0.5 mm	
Length and Width	ISO 10545-2	± 0.6 % / ± 2.0 mm	
Rectangularity	ISO 10545-2	± 0.5% / ± 2.0 mm	
Straightness of Sides	ISO 10545-2	± 0.5 % / ± 1.5 mm	
Water Absorption	ISO 10545-3	> 0.5%	
Breaking Strength	ISO 10545-4	> 1300 N	
Modulus of Rupture	ISO 10545-4	> 35 N/mm²	
Thermal Shock Resistance	ISO 10545-9	Pass	
Crazing Resistance	ISO 10545-11	Pass	
Frost Resistance	ISO 10545-11	Pass	
High Concentrations of Acids and Alkalis	ISO 10545-13	HB/HB/HB	HA/HA/HA
Low Concentrations of Acids and Alkalis	ISO 10545-13	LB/LB/LB	LA/LA/LA
Household Chemicals and Swimming Pool Salts	ISO 10545-13	A/A	
Surface Scratch Resistance		-	5
Stain Resistance	ISO 10545-14	5/-/5/5	
Dynamic Coefficient of Friction (DCOF)	ANSI A137	< 0.42	-
Slip Resistance Test (PTV) - Wet Conditions	BS-7976-2	+16	-
Slip Resistance (Pendulum Test)	UNE-ENV-12633	0	1

According to ANSI and MIA standards. depending on the type and size of tile. it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Glazed Porcelain Tile
- Matte | Polished | Premium Polished | Brushed/Shaped Finishes
- 6mm | 8mm | 10mm Thicknesses
- Rectified Edge
- PEI Rating = 4
- V3 - Moderate Variation
- Frost Resistance = Yes





[www.genrose.com](http://www.genrose.com)