







12" x 24" | 36" x 36" Field Tile in White 2" x 2" Mosaic in White

AVAILABLE STOCKED ITEMS:

Field Tiles	S		
SIZE	THICKNESS	FINISH	COLORS
12"x 24"	9.5mm	Matte Polished	White
36"x 36"	10.5mm	Matte Polished	White
Mosaics			
SHEET SIZE	ТҮРЕ	FINISH	COLORS
12"x 12"	2″x 2″ Mosaic	Matte	White
12"x 12"	Triangle Mosaic	Polished	White

All Sizes are Nominal.

MADE TO ORDER FIELD TILES AND MOSAICS:


Minimum quantity required. Contact your sales representative for more information.

This represents a small portion of the mosaic patterns we offer. We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	Any 24″ field tile can be cut down to		2" 4"		1³/8″x3″ 2″x4″
	a smaller size in any length and width combination with a 1″ minimum.	BRICKS		DIAMONDS	
			1"x2" 1"x3" 1 ³ / ₈ "x3" 2"x4"		2"
FIELD S	IELD SHAPES* CHEVRONS HERRINGBONE		GBONE		
Half Hexagon	6.7" Base		2"x12"		1"×2" 2"×4" ⁵ /8"×4"
Diamond	4"				
Hexagon Chevron	6" 2"x12" 6"x24"		GONS 2" w/ 0.6" Squares	HEXA	GONS 1 ¹ /8″ 2″
TRAPEZOID W/ DOT		SQUARES		RECTANGLES	
	4"x2 ¹ / ₂ " w/ ⁵ / ₈ " Dot		1"x1" 2"x2" 1³/8"x1³/8" 3"x3"		1"x2" 1"x4"

*Other sizes available upon request

MOSAICS:




White

Colors shown may vary from actual product. Final selection should be made from actual product samples. Products and availability are subject to change, please refer to our website for the most up to date selection.

White











2" x 2" Mosaic in White 12" x 24" Field Tile in White



Features	Test Method	Valu	Value	
Dimensions and Surface Quality	ISO 10545-2	Comp	Complies	
Water Absorption	ISO 10545-3	≤ 0.5	≤ 0.5 %	
Modulus of Rupture	ISO 10545-4	35 – 45 N/mm²		
Breaking Strength	ISO 10545-4	1,600 - 2,400 N		
Thermal Resistance	ISO 10545-9	Resistant		
Crazing Resistance	ISO 10545-11	Resistant		
Frost Resistance	ISO 10545-12	Resist	Resistant	
Chemical Resistance	ISO 10545-13	Polished A, GLB	Matte A, GLA	
Stain Resistance	ISO 10545-14	5		
Reaction to Fire	EN14411:2012	A1 _{FL} /	A1 _{FL} /A1	
		Polished	Matte	
DCOF (Wet)	-	≤ 0.42 Does Not Pass	≥ 0.42	
Recycled Material	-	31%		



This product will contribute to USGBC registered LEED V4.1 projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700. Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Glazed Porcelain Tile
- Matte | Polished Finishes
- 9.5mm | 10.5mm Thicknesses
- Rectified Edge
- PEI Rating = 4
- Frost Resistance = Yes
- V3 Moderate Variation



www.genrose.com



www.genrose.com