

MIDTOWN



GENROSE



For the most up-to-date product information, scan the QR code.

2" x 10" Floor/ Wall Tile in Light Grey and White



2" x 10" Floor/Wall Tile in Blu



2" x 10" Floor/Wall Tile in Light Grey



2" x 10" Floor/Wall Tile in White

AVAILABLE STOCKED ITEMS:

9.5mm Floor/Wall Tiles - Pressed Edge			
SIZE	FINISH		COLORS
2" x 10"	Matte		White Light Grey Blu Emerald
	Polished		White Light Grey Blu Emerald Black
9.5mm Trim Pieces - Pressed Edge			
SIZE	TYPE	FINISH	COLORS
0.2" x 10"	Finishing Strip	Matte	White Light Grey Blu
		Polished	White Light Grey Blu Emerald Black

AVAILABLE STOCKED ITEMS:

9.5mm Floor/Wall Tiles - Pressed Edge		
SIZE	FINISH	COLORS
2" x 10"	Matte	Black

- All Sizes are Nominal

COLORS:



White V1



Light Grey V2



Blu V2



Emerald V2




Black V1

Colors shown may vary from actual product. Final selection should be made from actual product samples. Products and availability are subject to change, please refer to our website for the most up to date selection.



GENROSE

MIDTOWN
Glazed Porcelain Tile

Features	Test Method	Value	
Dimensions	ISO 10545 - 2	Compliant	
Surface Quality		Min. 95% of tiles free of visible defects	
Water Absorption	ISO 10545 - 3	< 0.2%	
Modulus of Rupture / Bending Strength	ISO 10545 - 4	> 40 N/mm ²	
Breaking Strength		≥ 1300 N	
Coefficient of Linear Thermal Expansion	ISO 10545 - 8	a ≤ 7.1 x 10 ⁻⁶ °C ⁻¹	
Thermal Shock Resistance	ISO 10545 - 9	Resistant	
Crazing Resistance	ISO 10545 - 11	Resistant	
Chemical Resistance (Domestic)	ISO 10545 - 13	A	
Chemical Resistance (Low Concentration)		LA	
Chemical Resistance (High Concentration)		HA	
Fire Resistance	-	A1/A1 _{FL}	
Slip Resistance (Wet)	ANSI A326.3	Polished	Matte
		DCOF Does Not Pass	DCOF 0.43
LEED	-	Yes	
Recycled Content	-	≥ 50%	
VOC Emissions	-	Zero VOC	
Material Health Certification	-	Red List Free, Certificate Available	
Environmental Product Declaration	-	Facility-Specific	
<div><div></div><div>This product will contribute to USGBC registered LEED projects. It will also contricute to the ANSI approved NAHB Green Building Standard ICC 700.</div></div>			

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tilesin order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

- Product Info:**
- Glazed Porcelain Tile
 - Matte | Polished Finishes
 - V1 - Uniform Appearance (White | Black)
 - V2 - Slight Shading Variation (Light Grey | Blu | Emerald)
 - 9.5mm Thickness
 - Pressed Edge
 - Frost Resistance = Yes



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.

