

MONTAUK



For the most up-to-date product information, scan the QR code.

48" x 48" Field Tile in Iron
48" x 109" Slab in Iron



48"x 48" Field Tile in Sand
 48"x 48" Field Tile in Taupe
 48"x 109" Slab in Taupe



48"x 48" Field Tile in Oyster
 48"x 48" Field Tile in Graphite



24"x 48" Field Tile in Taupe
48"x 48" Field Tile in Lunar
48"x 110" Slab in Lunar



24"x 48" Field Tile in Graphite



24"x 48" Paver in Sand
48"x 109" Slab in Sand

AVAILABLE STOCKED ITEMS:

9mm Floor/Wall Tiles - Rectified Edge			
SIZE	FINISH	COLORS	
4" x 4"	Matte	Sand Lunar Taupe Iron Oyster Graphite	
4" x 12"	Matte	Sand Lunar Taupe Iron Oyster Graphite	
12" x 12"	Matte	Sand Lunar Taupe Iron Oyster Graphite	
12" x 24"	Matte	Sand Lunar Taupe Iron Oyster Graphite	
9mm Mosaics - Rectified Edge			
SHEET SIZE	MOSAIC TYPE	FINISH	COLORS
12" x 12"	2" x 2"	Matte	Sand Lunar Taupe Iron Oyster Graphite

SPECIAL ORDER ITEMS:

9mm Floor/Wall Tiles - Rectified Edge			
SIZE	FINISH	COLORS	
12" x 24"	Anti-Slip	Sand Iron	
24" x 24"	Anti-Slip	Sand Iron	
	Matte	Sand Lunar Taupe Iron Oyster Graphite	
24" x 48"	Anti-Slip	Sand Iron	
	Matte	Sand Lunar Taupe Iron Oyster Graphite	
39" x 39"	Matte	Sand Lunar Iron Oyster	
48" x 48"	Matte	Sand Lunar Taupe Iron Oyster Graphite	
6mm Slabs - Rectified Edge			
SIZE	FINISH	COLORS	
48" x 109"	Matte	Sand Lunar Iron Graphite	
20mm Outdoor Pavers - Rectified Edge			
SIZE	FINISH	COLORS	
24" x 24"	Anti-Slip	Sand Lunar Taupe Iron Oyster Graphite	
24" x 48"	Anti-Slip	Sand Lunar Taupe Iron Oyster Graphite	
39" x 39"	Anti-Slip	Sand Oyster	
48" x 48"	Anti-Slip	Sand Lunar Iron	
Trim Pieces - Rectified Edge			
SIZE	TYPE	FINISH	COLORS
3" x 24"	Bullnose	Matte	Sand Lunar Taupe Iron Oyster Graphite

All Sizes are Nominal.

COLORS:



Sand



Taupe



Oyster



Lunar



Iron



Graphite

Colors shown may vary from actual product. Final selection should be made from actual product samples. Products and availability are subject to change, please refer to our website for the most up-to-date selection.




















48" x 48" Field Tile in Iron
48" x 109" Slab in Iron

MADE TO ORDER FIELD TILES AND MOSAICS:

Minimum quantity required. Contact your sales representative for more information.

This represents a small portion of the mosaic patterns we offer.
We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		2" 4"		1 ³ / ₈ "x3" 2"x4"
		BRICKS		DIAMONDS	
			1"x2" 1"x3" 1 ³ / ₈ "x3" 2"x4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
 Half Hexagon	6.7" Base		2"x12"		1"x2" 2"x4" 5/ ₈ "x4"
 Diamond	4"				
 Hexagon	6"	OCTAGONS		HEXAGONS	
 Chevron	2"x12" 6"x24"		2" w/ 0.6" Squares		1 ¹ / ₈ " 2"
TRAPEZOID W/ DOT		SQUARES		RECTANGLES	
	4"x2 ¹ / ₂ " w/ ⁵ / ₈ " Dot		1"x1" 1 ³ / ₈ "x1 ³ / ₈ " 2"x2" 3"x3"		1"x2" 1"x4"





*Other sizes available upon request



GENROSE

MONTAUK

Color Body Porcelain Tile

Features	Test Method	Value		
Dimensions	ISO 10545 - 2	Compliant		
Surface Quality		Min. 95% of tiles free of visible defects		
Water Absorption	ISO 10545 - 3	< 0.1%		
Modulus of Rupture / Bending Strength	ISO 10545 - 4	9mm	20mm	
		> 35 N/mm ²	60.4 N/mm ²	
Breaking Strength		≥ 1,300 N	13,698 N	
Deep Abrasion Resistance	ISO 10545 - 6	≤ 150 mm ³	≤ 130 mm ³	
Coefficient of Linear Thermal Expansion	ISO 10545 - 8	< 7.1 10 ⁻⁶ °C ⁻¹		
Thermal Shock Resistance	ISO 10545 - 9	Resistant		
Crazing Resistance	ISO 10545 - 11	Resistant		
Chemical Resistance (Domestic)	ISO 10545 - 13	A		
Chemical Resistance (Low Concentration)		LA		
Chemical Resistance (High Concentration)		HA		
Fire Resistance	-	A1/A1 _{FL}		
Slip Resistance	ANSI A326.3	9mm Matte	9mm Anti-Slip	20mm Anti-Slip
		DCOF 0.61	DCOF 0.60	DCOF 0.61
LEED	-	Yes		
Recycled Content	-	> 30%		
VOC Emissions	-	Zero VOC		
Declare	-	Red List Free		
Environmental Product Declaration	-	Industry-Wide		
Health Product Declaration	-	Available		
<div></div> <div>This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.</div>				

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Color Body Porcelain Tile
- Matte | Anti-Slip Finishes
- 6mm | 9mm | 20mm Thickness
- Rectified Edge
- V3 - Moderate Variation
- Frost Resistance - Yes



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.



www.genrose.com