

ORACLE

 **GENROSE**





48"x111" 6mm Slab in Golden Onyx
48"x48" Field Tile in White Onyx



48"x48" Field Tile in White Blend
48"x48" Field Tile in White Porphyry



48"x48" Field Tile in White Porphyry



32"x32" Field Tile in Silver Blend
48"x95" 6mm Slab in Silver Onyx



48"x111" 6mm Slab in Golden Onyx
48"x48" Field Tile in Golden Porphyry



48"x48" Field Tile in White Blend

AVAILABLE IN:

10mm Field Tile

32"x71" Satin | Polished | Structured Finish
 32"x32" Satin | Polished | Structured Finish
 16"x32" Satin | Polished | Structured Finish
 24"x48" Satin | Polished | Structured Finish
 24"x24" Satin | Polished | Structured Finish

10mm Mosaics

2"x2" Satin | Polished | Structured Finish
 1"x1" Satin | Polished | Structured Finish
 12"x24" Sheet Modulo Listello Sfalsato Satin | Polished | Structured Finish

10mm Trim Pieces

2"x24" Bullnose Satin | Polished | Structured Finish

20mm Field Tile

24"x48" Structured Finish

6mm Slab

63"x126" Satin | Polished Finish
 48"x111" Satin | Polished Finish
 48"x95" Satin | Polished | Structured Finish

6mm Field Tile

63"x63" Satin | Polished Finish
 48"x48" Satin | Polished | Structured Finish
 24"x48" Satin | Polished | Structured Finish
 32"x32" Satin | Polished Finish

6mm Mosaics

3"x3" Satin | Polished | Structured Finish
 3"x6" Muretto Satin | Polished | Structured Finish









6mm Trim Pieces

2"x32" Bullnose Satin | Polished Finish

- All sizes are nominal.
- Onyx and Blend are only available in Satin and Polished Finish.
- Porphyry is only available in Structured Finish.

MADE TO ORDER FIELD TILES AND MOSAICS:

This represents a small portion of the mosaic patterns we offer.
 We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		2" 4"		1 3/8" x 3" 2" x 4"
			1" x 2" 1" x 3" 1 3/8" x 3" 2" x 4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
	Half Hexagon 6.7" Base		2" x 12"		1" x 2" 2" x 4" 5/8" x 4"
	Diamond 4"				
	Hexagon 6"				
	Chevron 2" x 12" 6" x 24"	OCTAGONS 2" w/ 0.6" Squares		HEXAGONS 1 1/8" 2"	
TRAPEZOID W/ DOT		SQUARES		RECTANGLES	
	4" x 2 1/2" w/ 5/8" Dot		1" x 1" 2" x 2" 1 3/8" x 1 3/8" 3" x 3"		1" x 2" 1" x 4"

*Other sizes available upon request



White Onyx

V3 



White Blend

V4 



White Porphyry

V4 



Golden Onyx

V3 



Golden Blend

V4 



Golden Porphyry

V4 



Silver Onyx

V3 



Silver Blend

V4 



Silver Porphyry

V4 

Colors shown may vary from actual product. Final selection should be made from actual product samples.



Features	Test Method	Value	
		10mm	6mm
Length and Width	ISO 10545-2	± 0.15%	± 0.15%
Admitted Thickness Deviation	ISO 10545-2	± 5%	± 5%
Maximum Straightness Deviation	ISO 10545-2	± 0.1%	± 0.1%
Maximum Right-Angle Deviation	ISO 10545-2	± 0.2%	± 0.2%
Flatness	ISO 10545-2	± 0.35%	± 0.2%
Surface Quality	ISO 10545-2	At least 95% of the tiles must be free from visible flaws	At least 95% of the tiles must be free from visible flaws
Water Absorbtion	ISO 10545-3	Average Value 0.08%	Average Value 0.08%
Breaking Strength	ISO 10545-4	Average Value 3200 N	Average Value 1350 N
Bending Strength	ISO 10545-4	average value 50 N/mm ²	average value 52 N/mm ²
Resistance to Deep Abrasion of Unglazed Tiles	ISO 10545-6	average value 140 mm ³	average value 140 mm ³
Thermal Shock Resistance	ISO 10545-9	Resistant	Resistant
Frost Resistance	ISO 10545-12	Resistant	Resistant
Resistance to Low Concentrations of Acids and Alkali	ISO 10545-13	ULA-ULB - GLOSSY ULA - SLATE-HAMMERED ULB - SATIN	ULA-ULB - GLOSSY ULA - SLATE-HAMMERED ULA-ULB - SATIN
Resistance to Domestic Chemicals and Additives for Swimming Pools	ISO 10545-13	UA	UA
Dynamic Coefficient of Friction	DCOF	> 0.42 wet SLATE-HAMMERED	> 0.42 wet SLATE-HAMMERED
Slip Resistance - Shoes	DIN-51130:2010	R10 - SLATE-HAMMERED	R10 - SLATE-HAMMERED
Slip Resistance - Barefoot	DIN-51097	Cl. B - SLATE-HAMMERED	Cl. B - SLATE-HAMMERED
Staining Resistance	ISO-10545-14	Cl. 4-5 - GLOSSY Cl. 5 - SLATE-HAMMERED Cl. 4-5 - SATIN	Cl. 4-5 - GLOSSY Cl. 5 - SLATE-HAMMERED Cl. 4-5 - SATIN
Release of Hazardous Substances	DM-1-2-2007-Reg-CE-1935-2004	-	Declared value for gl surfaces used on worktops
Recycled Material		10mm - 7.1% 6mm - 7.1% except for White Onyx Blend which are 0% 20mm - 12.5% for the White Porphyry and 76% for the Silver Golden Porphyry	
 This product is GREENGUARD® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.			
No VOC Emissions			

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Through Body Porcelain Tile
- Polished | Satin | Structured Finish
- 6mm | 10mm | 20mm Thicknesses
- Rectified Edge
- V3 - Moderate Variation | V4 - Substantial Variation
- Frost Resistance = Yes





www.genrose.com