PANE









24"x24" Field Tile in Naturale

AVAILABLE IN:

9mm Field Tiles

Rectified Edge

4"x12"Polished Finish8"x24"Polished Finish12"x24"Polished Finish24"x24"Polished Finish

- All sizes are NOMINAL

Deco

12"x24" Deco Polished Finish



This represents a small portion of the mosaic patterns we offer. We can cut any field tile to create a custom mosaic or field tile size as specified.

| FIELD TILES | | CUBES | | BASKETWEAVE | |
|----------------------------|-------------------------------------|----------|---------------------------------------------------------|-------------|---------------------------------------------|
| | N/A | | 2" 4" | | 1 ³ / ₈ "x3" 2"x4" |
| | | BRICKS | | DIAMONDS | |
| | | | 1"x2" 1"x3" 1 ³ /8"x3" 2"x4" | | 2" |
| FIELD SHAPES | | CHEVRONS | | HERRINGBONE | |
| Half Hexagon Diamond | N/A | | 2"x12" | | 1"x2" 2"x4" ⁵ /8"x4" |
| | | OCTAGONS | | HEXAGONS | |
| Hexagon Chevron | | | 2" w/ 0.6" Squares | | 1 ¹ /8" 2" |
| TRAPEZOID W/ DOT | | SQUARES | | RECTANGLES | |
| | 4"x21/2" w/ ⁵ /8" Dot | | 1"x1" 1 ³ /8"x1 ³ /8" 3"x3" | | 1"x2" 1"x4" |

Bianco



Fume



Bronzo

*Frames of Tile Not Available in Mosaics *Other sizes available upon request



Naturale



Acqua



12"x24" Deco





| Features | Test Methods | | Value | | |
|--------------------------------------------|---------------|---------------------------------------------------------------|--------------------|------------------------|--|
| Reaction to Fire | ISO 13501-1 | Class A1 _{fl} | | | |
| Length and Width | | ± 0.3% max 1mm | | | |
| Thickness | | ± 5% max 0.5mm | | | |
| Rectangularity | ISO 10545 - 2 | ± 0.3% max 0.8mm | | | |
| Wedging | | ± 0.3% max 1.5mm | | | |
| Warpage | | ± 0.4% max 1.8mm | | | |
| Water Absorption | ISO 10545 - 3 | 0.2% | | | |
| Flexual Strength | ISO 10545-4 | ≥ 35 N/mm² | | | |
| | | $S \ge 1300 \text{ N} \text{ (thickness} \ge 7.5 \text{ mm)}$ | | | |
| Coefficient of Restitution | ISO 10545-5 | Recommended value ≥ 0.55 | | | |
| Resistance to Deep Abrasion | ISO 10545-6 | ≤ 175 mm³ | | | |
| Coefficient of Thermal Linear Expansion | ISO 10545-8 | $\leq 7 \ 10^{-6} \bullet C^{-1}$ | | | |
| Thermal Shock Resistance | ISO 10545-9 | No Sample Must Show Visible Defects | | | |
| Moisture Expansion | ISO 10545-10 | ≤ 0.01 % (0.1 mm/m) | | | |
| Frost Resistance | ISO 10545-12 | Resistant | | | |
| Chemical Resistance | ISO 10545-13 | Household Chemicals | Low Concentrations | High Concentrations | |
| | | А | LA | Not Valid for Polished | |
| Stain Resistance | ISO 10545-14 | Resistant | | | |
| Lead and Cadmin Discharge | ISO 10545-15 | Pb < 0.01 mg/dm² Cd < 0.001 mg/dm² | | | |
| Slip Resistance | DIN 51130 | Failed | | | |

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Note: Not recommended for commercial and high-traffic residential flooring.

Product Info:

- Color Body Porcelain Tile
- Polished Finish
- 9mm Thickness
- Rectified Edge
- PEI Rating = 5 (Bianco/Naturale) | 4 (Bronzo/Fume) | 3 (Acqua)
- V1 Uniform Appearance
- Frost Resistance = Yes



www.genrose.com



www.genrose.com