

POMPANO



For the most up-to-date product information, scan the QR code.







24" x 48" Floor/Wall Tile in Pure | Fog





24" x 48" Floor/Wall Tile in Rope



# AVAILABLE STOCKED ITEMS:

9mm Floor/Wall Tiles - Rectified Edge			
SIZE	FINISH		COLORS
4" x 12"	Natural		Pure   Rope   Fog
24" x 24"	Natural		Pure   Rope   Fog
Floor/Wall Mosaic - Rectified Edge			
SHEET SIZE	TYPE	FINISH	COLORS
12" x 12"	2" x 2" Mosaic	Natural	Pure   Rope   Fog

# SPECIAL ORDER ITEMS:

9mm Floor/Wall Tiles - Rectified Edge		
SIZE	FINISH	COLORS
4" x 12"	Natural	Ocean Grey   Fossil
12" x 24"	Natural	Pure   Rope   Ocean Grey   Fossil   Fog
24" x 24"	Natural	Ocean Grey   Fossil
24" x 48"	Natural	Pure   Rope   Ocean Grey   Fossil   Fog
24" x 48"	Semi-Polished	Pure   Rope   Ocean Grey
48" x 48"	Natural	Pure   Rope   Ocean Grey
20mm Outdoor Pavers - Rectified Edge		
SIZE	FINISH	COLORS
24" x 24"	Natural	Pure   Rope   Fossil
24" x 48"	Natural	Pure   Rope   Fossil
48" x 48"	Natural	Pure   Rope   Fossil

All Sizes are Nominal.



















48" x 48" Floor/Wall Tile in Rope



# MADE TO ORDER FIELD TILES AND MOSAICS:

Minimum quantity required. Contact your sales representative for more information.

This represents a small portion of the mosaic patterns we offer.  
We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		2" 4"		1 <sup>3</sup> / <sub>8</sub> " x 3" 2" x 4"
BRICKS		DIAMONDS			
		1" x 2" 1" x 3" 1 <sup>3</sup> / <sub>8</sub> " x 3" 2" x 4"		2"	
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
 Half Hexagon	6.7" Base		2" x 12"		1" x 2" 2" x 4" 5 <sup>5</sup> / <sub>8</sub> " x 4"
 Diamond	4"				
 Hexagon	6"	OCTAGONS		HEXAGONS	
 Chevron	2" x 12" 6" x 24"		2" w/ 0.6" Squares		1 <sup>1</sup> / <sub>8</sub> " 2"
TRAPEZOID W/ DOT		SQUARES		RECTANGLES	
	4" x 2 <sup>1</sup> / <sub>2</sub> " w/ 5 <sup>5</sup> / <sub>8</sub> " Dot		1" x 1"      2" x 2" 1 <sup>3</sup> / <sub>8</sub> " x 1 <sup>3</sup> / <sub>8</sub> "      3" x 3"		1" x 2" 1" x 4"

\*Other sizes available upon request. All sizes are nominal.



24" x 48" Floor/Wall Tile in Pure | Fog  
48" x 48" Floor/Wall Tile in Pure | Fog



COLORS:



Pure



Rope



Ocean Grey



Fossil



Fog


2" x 2" MOSAIC



Pure



Rope



Fog

Colors shown may vary from actual product. Final selection should be made from actual product samples. Products and availability are subject to change, please refer to our website for the most up to date selection.




V2 



24" x 48" Floor/Wall Tile in Pure



Features	Test Method	Value		
<b>Length and Width</b>	ASTM C499	Complies with ANSI A 137.1 TAB. 10		
<b>Thickness</b>				
<b>Straightness of Sides</b>				
<b>Surface Flatness</b>				
<b>Rectangularity</b>				
<b>Surface Quality</b>		>95%		
<b>Water Absorption</b>	ISO 10545-3	≤0.05%		
<b>Modulus of Rupture / Bending Strength</b>	ISO 10545-4	≥ 35 N/mm <sup>2</sup>		
<b>Breaking Strength</b>	ISO 10545-4	≥ 1300 N		
<b>Surface Hardness (Mohs)</b>	EN 101	7		
<b>Resistance to Surface Abrasion</b>	ISO 10545-7	Class 4		
<b>Coefficient of Linear Thermal Expansion</b>	ISO 10545-8	< 7.1 x 10 <sup>-6</sup> °C <sup>-1</sup>		
<b>Thermal Shock Resistance</b>	ISO 10545-9	Resistant		
<b>Crazing Resistance</b>	ISO 10545-11	Resistant		
<b>Frost Resistance</b>	ISO 10545-12	Resistant		
<b>Chemical Resistance (Domestic)</b>	ISO 10545-13	A		
<b>Chemical Resistance (Low Concentration)</b>		LA		
<b>Chemical Resistance (High Concentration)</b>		HA		
<b>Stain Resistance</b>	ISO 10545-14	Class 5		
<b>Slip Resistance</b>	ANSI A137.1	Semi-Polished DCOF 0.56	Natural DCOF 0.72	Pavers DCOF 0.90
<b>Recycled Content</b>	-	> 40%		
<b>VOC Emissions</b>	-	Zero VOC		

This product will contribute to USGBC registered LEED projects.  
 It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Disclaimer:** DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

**Product Info:**

- Glazed Porcelain Tile
- Natural | Semi-Polished Finishes
- 9mm | 20mm Thicknesses
- Rectified Edge
- PEI Rating = 4
- Frost Resistance = Yes



**www.genrose.com**

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.



