

RHODES

 **GENROSE**





12"x24" Field Tile in Beige



12"x24" Field Tile in Bianco

AVAILABLE IN:

9mm Field Tiles

Pressed Edge

3"x12" Natural Finish

12"x12" Natural Finish

12"x24" Natural Finish

Trim Piece

3"x12"

Bullnose Natural Finish



Mosaic








2"x2" Mosaic Natural Finish

- All sizes are NOMINAL

MADE TO ORDER FIELD TILES AND MOSAICS:

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		2" 4"		1 3/8"x3" 2"x4"
		BRICKS		DIAMONDS	
			1"x2" 1"x3" 1 3/8"x3" 2"x4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
	Half Hexagon 6.7" Base		2"x12"		1"x2" 2"x4" 5/8"x4"
	Diamond 4"			HEXAGONS	
	Hexagon 6"	OCTAGONS			1 1/8" 2"
	Chevron 2"x12" 6"x24"		2" w/ 0.6" Squares		
TRAPEZOID W/ DOT		SQUARES		RECTANGLES	
	4"x2 1/2" w/ 5/8" Dot		1"x1" 1 3/8"x1 3/8" 2"x2" 3"x3"		1"x2" 1"x4"

*Other sizes available upon request



Bianco



Beige



Grigio

Colors shown may vary from actual product. Final selection should be made from actual product samples.

2"X2" MOSAIC



Bianco



Beige



Greigo



12"x12" Field Tile in Beige

Features	Test Method	Value		
		7 cm ≤ N < 15 cm	N ≥ 15 cm	
Sides	ISO 10545-2	± 0.9mm	± 0.6%	± 2mm
Thickness		± 0.5mm	± 5%	± 0.5mm
Straightness of Sides		± 0.8mm	± 0.5%	± 1.5mm
Rectangularity		± 0.8mm	± 0.5%	± 2mm
Surface Flatness		± 0.8mm	± 0.5%	± 2mm
Water Absorption		ISO 10545-3	≤ 0.1%	
Flexion Resistance	ISO 10545-4	R ≥ 35 N/mm S ≥ 700 N (N < 7.5 mm) S ≥ 1300 N (N ≥ 7.5mm)		
Impact Resistance	ISO 10545-5	> 0.8		
Coefficient of Linear Thermal Expansion	ISO 10545-8	6.7x10 ⁻⁶ /C°		
Thermal Shock Resistance	ISO 10545-9	Resistant		
Moisture Expansion	ISO 10545-10	MAX 0.1mm/m		
Frost Resistance	ISO 10545-12	Resistant		
Resistance to Household Chemical Products	ISO 10545-13	B Min		
Stain Resistance	ISO 10545-14	Class 3 Min		
Lead and Cadmium Discharge	ISO 10545-15	< Than Instrument Limit		
Skid Resistance	DM. 236/89 BCRA	> 0.4		
	ANSI A 137.1	> 0.42		
	DIN 51097	R9		
	DIN 51130	A+B MOSAICO		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Through Body Porcelain Tile
- Natural Finish
- 9mm Thickness
- Pressed Edge
- V3 - Moderate Variation
- Frost Resistance = Yes





www.genrose.com