

RIALTO



For the most up-to-date product information, scan the QR code.







24" x 48" Field Tile in Fog



24" x 24" Field Tile in Storm




















AVAILABLE STOCKED ITEMS:

9.5mm Field Tiles			
SIZE	FINISH		COLORS
12" x 24"	Matte		Rainbow   Fog   Cloud   Storm
24" x 24"	Matte		Rainbow   Fog   Cloud   Storm
24" x 48"	Matte		Rainbow   Fog   Cloud   Storm
36" x 36"	Matte		Rainbow   Fog   Cloud   Storm
9mm Trim Pieces			
SIZE	TYPE	FINISH	COLORS
3" x 24"	Bullnose	Matte	Rainbow   Fog   Cloud   Storm
12" x 24"	StairTread	Matte	Rainbow   Fog   Cloud   Storm

- All sizes are NOMINAL

MADE TO ORDER FIELD TILES AND MOSAICS:

This represents a small portion of the mosaic patterns we offer.  
We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		2" 4"		1 3⁄8"x3" 2"x4"
			1"x2" 1"x3" 1 3⁄8"x3" 2"x4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
	6.7" Base Half Hexagon		2"x12"		1"x2" 2"x4" 5⁄8"x4"
	4" Diamond				
	6" Hexagon		2" w/ 0.6" Squares	HEXAGONS	
	2"x12" Chevron				1 1⁄8" 2"
TRAPEZOID W/ DOT		SQUARES		RECTANGLES	
	4"x2.5" w/ 5⁄8" Dot		1"x1" 1 3⁄8"x1 3⁄8"		1"x2" 1"x4"

\*Other sizes available upon request



Rainbow



Fog



Cloud



Storm

Colors shown may vary from actual product. Final selection should be made from actual product samples.  
Products and availability are subject to change, please refer to our website for the most up to date selection.





24" x 48" Field Tile in Cloud

Features	Test Method	Fixed Value
Length And Width	ISO 10545-2	± 0.6% (± 2.00 mm)
Thickness		± 5% (± 0.5 mm)
Warpages Of Edges		± 0.5% (± 1.5 mm)
Wedging		± 0.5% (± 2.00 mm)
Flatness		± 0.5% (± 2.00 mm)
Water Absorption	ISO 10545-3	≤ 0.5%
Bending Strength	ISO 10545-4	≥ 35 N/ mm <sup>2</sup>
Breaking Strength		> 1300 N
Coefficient of Linear Thermal Expansion	ISO 10545-8	≈ 7X10 <sup>-6</sup> C <sup>-1</sup>
Thermal Shock Resistance	ISO 10545-9	Resistant
Frost Resistance	ISO 10545-12	Resistant
Resistance of Chemical Attack	ISO 10545-13	Resistant
Stain Resistance	ISO 10545-14	Class 3
Colors Resistance to Light	DIN 51094	No Alteration
Slip Resistance (DCOF)	ANSI 137.1	0.54
Recycled Content	-	≥ 10
DCOF	-	0.54

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide.

**Disclaimer:** DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

- Product Info:**
- Color Body Porcelain Tile
  - Matte Finish
  - 9.5 mm Thickness
  - Rectified Edge
  - V3 - Moderate Variation
  - PEI Rating 5
  - Frost Resistance = Yes

[www.genrose.com](http://www.genrose.com)

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.



[www.genrose.com](http://www.genrose.com)