



12"x 24" Field Tile in White 36"x 36" Field Tile in White 2"x 2" Mosaic in White

AVAILABLE STOCKED ITEMS:

Field Tiles							
SIZE	THICKNESS	FINISH	COLORS				
12" x 24"	9.5mm	Matte Polished	White Sand Pearl				
36" x 36"	10.5mm	Matte Polished	White Sand Pearl				
10.5mm Field	Deco						
SIZE	FI	NISH	COLORS				
24" x 48"	Polished		White Sand Pearl				
9.5mm Mosaid	cs						
SHEET SIZE	TYPE	FINISH	COLORS				
12" x 12"	2" x 2" Mosaic	Matte	White Sand Pearl				
12.8" x 8.86"	Hex Mosaic	Polished	White Sand Pearl				

SPECIAL ORDER ITEMS:

10.5mm Field Tiles						
SIZE	FINISH	COLORS				
24"× 48"	Matte Polished	White Sand Pearl				

MADE TO ORDER FIELD TILES AND MOSAICS: Minimum quantity required. Contact your sales representative for more information.

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD	TILES	CUBES		BASKETWEAVE	
	Any 24" field tile		2" 4"		1³/ ₈ ″x3″ 2″x4″
	a smaller size in any length and width combination with a 1" minimum.	BRICKS		DIAMONDS	
			1"x2" 1"x3" 1 ³ / ₈ "x3" 2"x4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
Half Hexagon	6.7" Base		2"x12"		1"x2" 2"x4" ⁵ /8"x4"
Diamond	4"			* > > >	
		OCTAGONS		HEXAGONS	
Hexagon Chevron	6" 2"x12"		2" w/ 0.6" Squares		1¹/8″ 2″
	6"x24"	*****			
TRAPEZO	ID W/ DOT	SQUARES		RECTANGLES	
	4"x2 ¹ / ₂ " w/ ⁵ / ₈ " Dot		1"x1" 2"x2" 1 ³ / ₈ "x1 ³ / ₈ " 3"x3"		1"x2" 1"x4"





Pearl





Sand White

2" X 2" MOSAICS







White

HEX MOSAICS







24" X 48" FIELD DECOS







Pearl Sand Wh





Features	Test Method	Value	
Dimensions and Surface Quality	ISO 10545-2	Complies	
Water Absorption	ISO 10545-3	≤ 0.5 %	
Modulus of Rupture	ISO 10545-4	35 – 45 N/mm²	
Breaking Strength	ISO 10545-4	1,600 - 2,400 N	
Thermal Resistance	ISO 10545-9	Resistant	
Crazing Resistance	ISO 10545-11	Resis	ant
Frost Resistance	ISO 10545-12	Resistant	
Chemical Resistance	ISO 10545-13	Polished	Matte
Chombal Noolsands	100 100 10	A, GLB	A, GLA
Stain Resistance	ISO 10545-14	5	
Reaction to Fire	EN 14411:2012	A1 _{FL} /A1	
DCOF (Wet)	-	Non-Compliant	
Recycled Material	-	31%	







This product will contribute to USGBC registered LEED V4.1 projects.

It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Porcelain Tile
- Matte | Polished Finish
- 10.5mm | 9.5mm Thicknesses
- Rectified Edge
- PEI Rating = 4
- Frost Resistance = Yes
- V3 Moderate Variation



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.



www.genrose.com