

SUAVE

 GENROSE



AVAILABLE IN:

9mm Field Tiles

Rectified Edge

- 3"x12" Polished Finish
- 6"x12" Matte Finish
- 12"x24" Matte | Polished Finish
- 24"x24" Matte | Polished Finish
- 24"x48" Matte | Polished Finish

Mosaics







- 2"x2" Mosaic
 - 5/8"x4" Herringbone Mosaic
 - 4" Hexagon Mosaic
- Matte Finish
 Polished Finish
 Matte Finish

- All sizes are NOMINAL

MADE TO ORDER FIELD TILES AND MOSAICS:

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

| FIELD TILES | | CUBES | | BASKETWEAVE | |
|---|---|---|--|---|---------------------------|
|  | Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum. |  | 2" 4" |  | 1 3/8"x3" 2"x4" |
|  | | BRICKS | | DIAMONDS | |
| | |  | 1"x2" 1"x3" 1 3/8"x3" 2"x4" |  | 2" |
| FIELD SHAPES* | | CHEVRONS | | HERRINGBONE | |
|  Half Hexagon | 6.7" Base |  | 2"x12" |  | 1"x2" 2"x4" 5/8"x4" |
|  Diamond | 4" | OCTAGONS | | HEXAGONS | |
|  Hexagon | 6" |  | 2" w/ 0.6" Squares |  | 1 1/8" 2" |
|  Chevron | 2"x12" 6"x24" | SQUARES | | RECTANGLES | |
|  | 4"x2 1/2" w/ 5/8" Dot |  | 1"x1" 2"x2" 1 3/8"x1 3/8" 3"x3" |  | 1"x2" 1"x4" |


*Other sizes available upon request


White

Oro

White 4" Hexagon Mosaic

Oro 4" Hexagon Mosaic

White 2"x2" Mosaic

Oro 2"x2" Mosaic

White 5/8"x4" Herringbone Mosaic

Oro 5/8"x4" Herringbone Mosaic

Colors shown may vary from actual product. Final selection should be made from actual product samples.

V3 

| Features | Test Method | Value | |
|---------------------------------|--------------|-----------|----------|
| | | Matte | Polished |
| DCOF (Wet) | ANSI A 326.3 | ≥ 0.42 | N/A |
| Breaking Strength | ANSI C648 | ≥ 425 lbf | |
| Scratch Hardness (MOHS) | - | 7 | |
| Water Absorption | ASTM C373 | < 0.5% | |
| Chemical Resistance | ASTM C650 | Class A | Class E |
| Abrasion Resistance | ASTM C1027 | Class 3 | |
| Thermal Shock Resistance | ASTM C484 | Resistant | |
| Frost Resistance | ASTM C1026 | Resistant | |

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Glazed Porcelain Tile
- Matte | Polished Finishes
- 9mm Thickness
- Rectified Edge
- PEI Rating = 3 (12"x24' Matte | Polished)
- V3 - Moderate Variation
- Frost Resistance = Yes



www.genrose.com



www.genrose.com