

SWIRL

 **GENROSE**





16"x48" Wall Tile
16"x48" Wall Tile Deco



32"x32" Field Tile
16"x48" Wall Tile
16"x48" Wall Tile Deco

AVAILABLE IN:

9mm Field Tiles + Decos

Rectified Edge

24"x24" Matte Finish

32"x32" Matte Finish

10mm Wall Tile + Decos

Rectified Edge

16"x48" Glossy Finish

16"x48" Deco Glossy Finish

Trim Pieces

12" Quartino Glossy Finish









- All sizes are NOMINAL

MADE TO ORDER FIELD TILES AND MOSAICS: Available for 9mm tiles only

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		2" 4"		1 ³ / ₈ "x3" 2"x4"
		BRICKS		DIAMONDS	
			1"x2" 1"x3" 1 ³ / ₈ "x3" 2"x4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
 Half Hexagon	6.7" Base		2"x12"		1"x2" 2"x4" 5/8"x4"
 Diamond	4"	OCTAGONS		HEXAGONS	
 Hexagon	6"		2" w/ 0.6" Squares		1 ¹ / ₈ " 2"
 Chevron	2"x12" 6"x24"	SQUARES		RECTANGLES	
	4"x2 ¹ / ₂ " w/ 5/8" Dot		1"x1" 1 ³ / ₈ "x1 ³ / ₈ " 2"x2" 3"x3"		1"x2" 1"x4"

*Other sizes available upon request



Bianco Versilia



Bianco Versilia

Features	Test Method	Value		
Sides	ISO 10545-2	7 cm ≤ N < 15cm	N ≥ 15 cm	
		± 0.75 mm	± 0.5% (± 2.0 mm)	
Thickness		± 0.5 mm	± 10% (± 0.5 mm)	
Straightness of Sides		± 0.5 mm	± 0.3% (± 1.5 mm)	
Rectangularity		± 0.75 mm	± 0.5% (± 2.0 mm)	
Surface Flatness		+ 0.75 mm - 0.5 mm	+ 0.5% (+ 2.0 mm) - 0.3% (- 1.5 mm)	
		+ 0.75 mm - 0.5 mm	+ 0.5% (+ 2.0 mm) - 0.3% (- 1.5 mm)	
		+ 0.75 mm	± 0.5% (± 2.0 mm)	
Water Absorption		ISO 10545-3	10% < E _b ≤ 20%	
Flexon Resistance		ISO 10545-4	> 600 N > 12 N/mm ²	
Impact Resistance	ISO 10545-5	> 0.6		
Coefficient of Linear Thermal-Expansion	ISO 10545-8	α = 6.7x10 ⁻⁶ /C°		
Resistance to Thermal Shocks	ISO 10545-9	No Damage		
Moisture Expansion (In mm/m)	ISO 10545-10	MAX 0.2 mm/m		
Resistance to Household and Swimming Pool Chemical Products	ISO 10545-13	GB Min		
Resistance to Low Concentrations of Acids and Alkali		Complying		
Resistance to High Concentrations of Acids and Alkali		Complying		
Stain Resistance	ISO 10545-14	Class 3 Min		
Lead and Cadmium Discharge	ISO 10545-15	< Than Instrument Limit		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Ceramic Tile | Through Body Porcelain Tile
- Matte | Glossy Finishes
- 9mm | 10mm Thickness
- Rectified Edge
- PEI Rating = 5 (Square Tiles)
- V2 - Slight Shading Variation
- Frost Resistance = Yes (Square Tiles) No = Deco | Quartino

Features	Test Method	Value	
Sides	ISO 10545-2	7 cm ≤ N < 15cm	N ≥ 15 cm
		± 0.9 mm	± 0.6% (± 2.0 mm)
± 0.5 mm		± 5.0% (± 0.5 mm)	
Straightness of Sides		± 0.75 mm	± 0.5% (± 1.5 mm)
Rectangularity		± 0.75 mm	± 0.5% (± 2.0 mm)
Surface Flatness		+ 0.75 mm	+ 0.5% (+ 2.0 mm)
Water Absorption		ISO 10545-3	≤ 0.1%
Flexon Resistance	ISO 10545-4	S ≥ 1.300 N R ≥ 35 N/mm ²	
Impact Resistance	ISO 10545-5	> 0.8	
Abrasion Resistance	ISO 10545-6	≤ 175 mm ³	
Coefficient of Linear Thermal-Expansion	ISO 10545-8	∂ = 6.7x10 ⁻⁶ /C°	
Resistance to Thermal Shocks	ISO 10545-9	No Damage	
Moisture Expansion (In mm/m)	ISO 10545-10	MAX 0.1 mm/m	
Frost Resistance	ISO 10545-12	No Damage	
Resistance to Household and Swimming Pool Chemical Products	ISO 10545-13	Complying	
Resistance to Low Concentrations of Acids and Alkali		Complying	
Resistance to High Concentrations of Acids and Alkali		Complying	
Stain Resistance	ISO 10545-14	Complying	
Lead and Cadmium Discharge	ISO 10545-15	< Than Instrument Limit	
Skid Resistance	DM. 236/89 BCRA	> 0.40	
	ANSI A 137.1	> 0.42	
	DIN 51130	R9	

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.





www.genrose.com