

SYDNEY





20"x40" Field Tile in Ivory



40"x40" Field Tile in Anthracite

AVAILABLE IN:

Field Tile


- 40"x40" *Matte | Anti-Slip Finish*
- 24"x24" *Matte Finish*
- 20"x40" *Matte Finish*

Mosaics


- 2"x2" *Mosaic Matte Finish*

Trim Pieces


Baseboard




Step



Rounded Step



















Stairtread



- All sizes are NOMINAL

MADE TO ORDER FIELD TILES AND MOSAICS:

This represents a small portion of the mosaic patterns we offer.
We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		2" 4"		1 ³ / ₈ " x3" 2" x4"
		BRICKS		DIAMONDS	
			1" x2" 1" x3" 1 ³ / ₈ " x3" 2" x4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
 Half Hexagon	6.7" Base		2" x12"		1" x2" 2" x4" 5/ ₈ " x4"
 Diamond	4"				
 Hexagon	6"				
 Chevron	2" x12" 6" x24"				
		OCTAGONS		HEXAGONS	
			2" w/ 0.6" Squares		1 ¹ / ₈ " 2"
TRAPEZOID W/ DOT		SQUARES		RECTANGLES	
	4" x2 ¹ / ₂ " w/ 5/ ₈ " Dot		1" x1" 1 ³ / ₈ " x1 ³ / ₈ " 2" x2" 3" x3"		1" x2" 1" x4"



20"x40" Field Tile in Ivory

Features	Test Method	Value
Length and Width	ISO 10545-2	± 0.9 mm ± 2.0 mm (± 0.6%)
Thickness	ISO 10545-2	± 0.5 mm ± 0.5 mm (± 5%)
Straightness of Sides	ISO 10545-2	± 0.75 mm ± 1.5 mm (± 0.5%)
Rectangularity	ISO 10545-2	± 0.75 mm ± 2.0 mm (± 0.5%)
Surface Flatness	ISO 10545-2	± 0.75 mm ± 2.0 mm (± 0.5%)
Surface Quality	ISO 10545-2	A minimum of 95% of the tiles shall be free from visible defects that would impair the appearance of a major area of tiles.
Water Absorption	ISO 10545-3	E _b ≤ 0.2%
Breaking Strength	ISO 10545-4	>2.800 N
Modulus Of Rupture	ISO 10545-4	> 44 N/mm ²
Abrasion Resistance	ISO 10545-7	Anthracite CLASS 2 Ivory CLASS 4 Grey CLASS 3
Coefficient of Linear Thermal Expansion	ISO 10545-8	6.1- 6.9 x10 ⁻⁶ (°C ⁻¹)
Thermal Shock Resistance	ISO 10545-9	Resistant
Crazing Resistance	ISO 10545-11	Resistant
Frost Resistance	ISO 10545-12	Resistant
Bond Strength / Adhesion. for: Cementitious Adhesives	12004:2007 +A1: 2012. 4.1	Type C2 >1 N/mm ²
Reaction to Fire		A1 _{FL} /A1
Chemical Resistance	ISO 10545-13	GA
Stain Resistance	ISO 10545-14	5
Recycled Material	-	43%

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

- Product Info:**
- Glazed Porcelain Tile
 - Matte | Anti-Slip Finishes
 - 10mm Thickness
 - Rectified Edge
 - PEI Rating = 4 (Ivory) | 3 (Grey) | 2 (Anthracite)
 - V2 - Slight Shading Variation
 - Frost Resistance = Yes





www.genrose.com