# **URBANA**







18"x36" Field Tile in Melted Ice



### **AVAILABLE IN:**

#### **8mm Field Tiles**

6"x36" Honed | Rigato Finish Rectified Edge\*

12"x24" Honed Finish Pressed Edge

18"x36" Honed | Rigato Finish Rectified Edge\*\*

#### Mosaic

2"x2" Mosaic Honed Finish

#### **Trim Pieces**

3"x24" Bullnose Honed Finish 6"x12" Cove Base Honed Finish

### MADE TO ORDER FIELD TILES AND MOSAICS:

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	Any 24" field tile		2" 4"		1 <sup>3</sup> / <sub>8</sub> "x3" 2"x4"
	a smaller size in any length and width	BRICKS		DIAMONDS	
	combination with a 1" minimum.		1"x2" 1"x3" 1 <sup>3</sup> / <sub>8</sub> "x3" 2"x4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
Half Hexagon	6.7" Base		2"x12"		1"x2" 2"x4" <sup>5</sup> / <sub>8</sub> "x4"
Diamond	4"				
Haveger	6"	OCTAGONS		HEXAGONS	
Hexagon  Chevron	0 2"x12" 6"x24"		2" w/ 0.6" Squares		1 <sup>1</sup> / <sub>8</sub> " 2"
TRAPEZOID W/ DOT		SQUARES		RECTANGLES	
	4"x2 <sup>1</sup> / <sub>2</sub> " w/ <sup>5</sup> / <sub>8</sub> " Dot		1"x1" 2"x2" 1 <sup>3</sup> / <sub>8</sub> "x1 <sup>3</sup> / <sub>8</sub> " 3"x3"		1"x2" 1"x4"

<sup>\*</sup>Other sizes available upon request

<sup>\*</sup>Not available in Weathered Black | Sage

<sup>\*\*</sup>Not available in Sage Rigato Finish

<sup>-</sup> All sizes are NOMINAL



Melted Ice Honed Finish



**Aqua** Honed Finish



Weathered Black Honed Finish



Sage Honed Finish



Melted Ice Rigato Finish



**Aqua** Rigato Finish



Weathered Black Rigato Finish

## 2"X2" MOSAIC







Aqua



Sage



**Weathered Black** 

# **TRIM PIECES**







Bullnose





Features	ASTM Test Method	Value	
Water Absorption	C373	≤ 0.1%	
Bond Strength	C482	≥ 200 psi	
Warpage Average	C485	≤ ± 0.40%	
Thickness Dimension	C499	≤ ± 0.04 in	
Facial Dimension		≤ ± 0.25%	
Wedging Average	C502	≤ ± 0.25%	
Breaking Strength	C648	≥ 400 lbf	
Chemical Resistance	C650	Class A	
Frost Resistance	C1026	Resistant	
Visible Abrasion Resistance for Glazed Tile	C1027	Class 4	
Stain Resistance	C1378	Class A*	
Hardness (Mohs)	Scratch Test (Not regulated)	≥ 7	
Coefficient of Friction (Dynamic)	DCOF Acutest (wet)	Honed Finish ≥ 0.50 Rigato Finish ≥ 0.65	
Recycled Material	-	≥ 40%	



This product is GREENGUARD® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

#### **Product Info:**

- Color Body Porcelain Tile
- Honed | Rigato Finish
- 8mm Thickness
- Rectified | Pressed Edge
- Frost Resistance = Yes
- PEI Rating = 4
- V2 Slight Shading Variation





www.genrose.com

<sup>\*</sup>All values given are for matte or honed material. No values are given for polished material. GENROSE does not recommend polished surfaces in areas subject to exposure from grease, oil or water.



www.genrose.com