VALDEZ







For the most up-to-date product information, scan the QR code.





12" x 24" Field Tile in Natural

AVAILABLE STOCKED ITEMS:

8.8mm Floor/Wall Tiles - Rectified Edge						
SIZE	FINISH		COLORS			
12" x 24"	Matte		White Beige Blue Natural			
8.8mm Mosaics - Rectified Edge						
SHEET SIZE	TYPE	FINISH	COLORS			
12" x 12"	2" × 2"	Matte	White Beige Blue Natural			

All Sizes are Nominal.

COLORS:







Natural



Beige



Blue




Colors shown may vary from actual product. Final selection should be made from actual product samples. Products and availability are subject to change, please refer to our website for the most up to date selection.

2" x 2" MOSAICS:









White Beige Natural Blue

MADE TO ORDER FIELD TILES AND MOSAICS:

Minimum quantity required. Contact your sales representative for more information.

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
a le	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		2" 4"		1 ³ / ₈ "x3" 2"x4"
		BRICKS		DIAMONDS	
			1"x2" 1"x3" 1 ³ / ₈ "x3" 2"x4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
Half Hexagon	6.7" Base		2"x12"		1"x2" 2"x4"
○ Diamond	4"			\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	⁵ / ₈ "x4"
		OCTAGONS		HEXAGONS	
_\rightarrow Hexagon	6"		2"		41/1
Chevron	2"×12" 6"×24"		w/ 0.6" Squares		1 ¹ / ₈ " 2"
TRAPEZOID W/ DOT		SQUARES		RECTANGLES	
	4"x2 ¹ / ₂ " w/ ⁵ / ₈ " Dot		1"x1" 2"x2" 1 ³ / ₈ "x1 ³ / ₈ " 3"x3"		1"x2" 1"x4"

^{*}Other sizes available upon request



12" x 24" Field Tile in Beige



VALDEZ Color Body Porcelain Tile

Features	Test Method	Value	
Dimensions	ISO 10545 - 2	Compliant	
Surface Quality	150 10545 - 2	Min. 95% of surface free of visible defects	
Water Absorption	ISO 10545 - 3	≤ 0.3%	
Modulus of Rupture / Bending Strength	ISO 10545 - 4	≥ 400 lb/ft²	
Breaking Strength	150 10343 - 4	> 1300 N	
Coefficient of Linear Thermal Expansion	ISO 10545 - 8	≤ 7.1 x 10 ⁻⁶ °C ⁻¹	
Thermal Shock Resistance	ISO 10545 - 9	Resistant	
Crazing Resistance	ISO 10545 - 11	Resistant	
Chemical Resistance (Domestic)		UA	
Chemical Resistance (Low Concentration)	ISO 10545 - 13	ULA	
Chemical Resistance (High Concentration)		UHA	
Fire Resistance	-	A1/A1 _{FL}	
Slip Resistance	ANSI A137.1	DCOF 0.60	
LEED		Yes	
VOC Emissions	-	Zero VOC	
Recycled Content	-	≥ 30%	
Environmental Product Declaration	-	Facility-Specific	







This product will contricute to USGBC registered LEED projects. It will also contricute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

- Product Info:
 Color Body Porcelain Tile
 Matte Finish
 8.8mm Thickness
 Rectified Edge
 V4 EXTREME Variation
- Frost Resistance = Yes



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.



www.genrose.com