

VELINO



For the most up-to-date product information, scan the QR code.

24" x 48" Floor/Wall Tile in Grigio



24" x 48" Floor/Wall Tile in Bianco
2" x 2" Intreccio Floor/Wall Mosaic in Bianco



24" x 48 " Floor/Wall Tile in Azzurro



12" x 24" | 24" x 48" Floor/Wall Tile in Beige
3" Hexagon Floor/Wall Mosaic in Beige



12" x 24" Floor/ Wall Tile in Grigio
2" x 2" Intreccio Floor/Wall Mosaic in Grigio



12" x 24" Floor/Wall Tile in Azzurro
3" Hexagon Floor/Wall Mosaic in Azzurro

AVAILABLE STOCKED ITEMS:

9.5mm Floor/Wall Tiles - <i>Rectified Edge</i>			
SIZE	FINISH		COLORS
12" x 24"	Natural		Bianco Azzurro Grigio Beige
24" x 48"			
9.5mm Floor/Wall Mosaics - <i>Rectified Edge</i>			
SHEET SIZE	MOSAIC TYPE	FINISH	COLORS
12" x 12"	2" x 2" Intreccio	Natural	Bianco Azzurro Grigio Beige
12" x 12"	3" Hexagon		

SPECIAL ORDER ITEMS:

9.5mm Floor/Wall Tiles - <i>Rectified Edge</i>		
SIZE	FINISH	COLORS
48" x 48"	Natural	Bianco Azzurro Grigio Beige

All Sizes are Nominal.



12" x 24" Floor/Wall Tile in Bianco

COLORS:



Bianco



Grigio



Azzurro



Beige

Colors shown may vary from actual product. Final selection should be made from actual product samples. Products and availability are subject to change, please refer to our website for the most up to date selection.

INTRECCIO MOSAIC: 2” X 2”



Bianco Grigio Azzurro Beige

HEXAGON MOSAIC: 3”



Bianco Grigio Azzurro Beige



12” x 24” Floor/Wall Tile in Bianco

Features	Test Method	Value
Dimensions	ISO 10545 - 2	Compliant
Surface Quality		Min. 95% of tiles free of visible defects
Warpage		Compliant
Wedging		Compliant
Water Absorption	ISO 10545 - 3	≤ 0.1%
Modulus of Rupture / Bending Strength	ISO 10545 - 4	R ≥ 35 N/mm ²
Breaking Strength		S ≥ 1300 N
Resistance to Surface Abrasion	ISO 10545 - 7	Class 4
Thermal Shock Resistance	ISO 10545 - 9	Resistant
Crazing Resistance	ISO 10545 - 11	Resistant
Chemical Resistance (Domestic)	ISO 10545 - 13	A
Chemical Resistance (Low Concentration)		LA
Chemical Resistance (High Concentration)		HA
Fire Resistance	-	A1/A1 _{FL}
Slip Resistance (Wet)	ANSI A326.3	DCOF 0.48
LEED	-	Yes
VOC Emissions	-	Zero VOC
Recycled Content	-	27%
Environmental Product Declaration	-	Yes
 This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8” wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16” wide. Please refer to TCNA guidelines for more on grout recommendations.

