# VELINO

GENROSE



For the most up-to-date product information, scan the QR code.

24" x 48" Floor/Wall Tile in Grigio



24″ x 48″ Floor/Wall Tile in Bianco
2″ x 2″ Intreccio Floor/Wall Mosaic in Bianco



24″ x 48 ″ Floor/Wall Tile in Azzurro




12″ x 24″ | 24″ x 48″ Floor/Wall Tile in Beige
3″ Hexagon Floor/Wall Mosaic in Beige



12″ x 24″ Floor/ Wall Tile in Grigio
2″ x 2″ Intreccio Floor/Wall Mosaic in Grigio



12″ x 24″ Floor/Wall Tile in Azzurro
3″ Hexagon Floor/Wall Mosaic in Azzurro

## AVAILABLE STOCKED ITEMS:

| **9.5mm Floor/Wall Tiles -** *Rectified Edge* | | | |
|---|---|---|---|
| **SIZE** | **FINISH** | | **COLORS** |
| 12″ x 24″ | Natural | | Bianco \| Azzurro \| Grigio \| Beige |
| 24″ x 48″ | | | |
| **9.5mm Floor/Wall Mosaics -** *Rectified Edge* | | | |
| **SHEET SIZE** | **MOSAIC TYPE** | **FINISH** | **COLORS** |
| 12″ x 12″ | 2″ x 2″ Intreccio | Natural | Bianco \| Azzurro \| Grigio \| Beige |
| 12″ x 12″ | 3″ Hexagon | | |

## SPECIAL ORDER ITEMS:

| **9.5mm Floor/Wall Tiles -** *Rectified Edge* | | |
|---|---|---|
| **SIZE** | **FINISH** | **COLORS** |
| 48″ x 48″ | Natural | Bianco \| Azzurro \| Grigio \| Beige |

All Sizes are Nominal.



12″ x 24″ Floor/Wall Tile in Bianco

## COLORS:



**Bianco**



**Grigio**



**Azzurro**



**Beige**

Colors shown may vary from actual product. Final selection should be made from actual product samples.
Products and availability are subject to change, please refer to our website for the most up to date selection.

## INTRECCIO MOSAIC: 2” X 2”



Bianco



Grigio



Azzurro



Beige

## HEXAGON MOSAIC: 3”



Bianco



Grigio



Azzurro



Beige



12” x 24” Floor/Wall Tile in Bianco

GENROSE

**VELINO**
Glazed Porcelain Tile

| Features | Test Method | Value |
|---|---|---|
| **Dimensions** | ISO 10545 - 2 | Compliant |
| **Surface Quality** | | Min. 95% of tiles free of visible defects |
| **Warpage** | | Compliant |
| **Wedging** | | Compliant |
| **Water Absorption** | ISO 10545 - 3 | ≤ 0.1% |
| **Modulus of Rupture / Bending Strength** | ISO 10545 - 4 | R ≥ 35 N/mm$^2$ |
| **Breaking Strength** | | S ≥ 1300 N |
| **Resistance to Surface Abrasion** | ISO 10545 - 7 | Class 4 |
| **Thermal Shock Resistance** | ISO 10545 - 9 | Resistant |
| **Crazing Resistance** | ISO 10545 - 11 | Resistant |
| **Chemical Resistance (Domestic)** | ISO 10545 - 13 | A |
| **Chemical Resistance (Low Concentration)** | | LA |
| **Chemical Resistance (High Concentration)** | | HA |
| **Fire Resistance** | - | A1/A1$_{FL}$ |
| **Slip Resistance (Wet)** | ANSI A326.3 | DCOF 0.48 |
| **LEED** | - | Yes |
| **VOC Emissions** | - | Zero VOC |
| **Recycled Content** | - | 27% |
| **Environmental Product Declaration** | - | Yes |

This product will contribute to USGBC registered LEED projects.
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8” wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16” wide. Please refer to TCNA guidelines for more on grout recommendations.

**Disclaimer:** DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

**Product Info:**

- Glazed Porcelain Tile
- Natural Finish
- 9.5mm Thickness
- Rectified Edge
- V2 - Slight Variation
- Frost Resistant

**www.genrose.com**

**Contact your sales representative for more information.** All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.



www.genrose.com