

WOODSTOCK





6"x36" Field Tile in Beachcomber



Statuario Marquetry Mosaic in Beachcomber
8"x48" Field Tile in Beachcomber | Grey Ridge



4"x24" Field Tile in Grey Ridge | Beachcomber



6"x36" Field Tile in Paper Birch



8"x48" Field Tile in Ash

4"x24" Field Tile in Sequoia

AVAILABLE IN:

Field Tiles

Rectified Edge

8"x48" 12mm Matte Finish

6"x36" 9mm Matte Finish

4"x24" 9mm Matte Finish

Mosaics

Marquetry Matte Finish

Statuario Marquetry Matte Finish*










- All sizes are NOMINAL

* Only available in Beachcomber | Sequoia | Grey Ridge

MADE TO ORDER FIELD TILES AND MOSAICS:

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		2" 4"		1 ³ / ₈ "x3" 2"x4"
			BRICKS 1"x2" 1"x3" 1 ³ / ₈ "x3" 2"x4"		DIAMONDS 2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
	Half Hexagon 6.7" Base		2"x12"		1"x2" 2"x4" 5 ¹ / ₈ "x4"
	Diamond 4"	OCTAGONS		HEXAGONS	
	Hexagon 6"		2" w/ 0.6" Squares		1 ¹ / ₈ " 2"
	Chevron 2"x12" 6"x24"	SQUARES		RECTANGLES	
	TRAPEZOID W/ DOT 4"x2 ¹ / ₂ " w/ 5 ¹ / ₈ " Dot		1"x1" 2"x2" 1 ³ / ₈ "x1 ³ / ₈ " 3"x3"		1"x2" 1"x4"

*Other sizes available upon request



Ash



Beachcomber



Paper Birch



French Oak



Grey Ridge



Sequoia

Colors shown may vary from actual product. Final selection should be made from actual product samples.

MARQUETRY MOSAIC



Sequoia Grey Ridge Beachcomber Ash French Oak Paper Birch

STATUARIO MARQUETRY MOSAIC



Sequoia Grey Ridge Beachcomber



WOODSTOCK
Glazed Porcelain Tile

Features	Test Method	Value
Water Absorption	ISO 10545-3	≤ 0.5
Abrasion Resistance	ISO 10545-7	4
Scratch Hardness	-	7
Breaking Strength	ISO 10545-4	≥ 300
Chemical Resistance	ISO 10545-13	Class A – Res.
Frost Resistance	ISO 10545-12	Resistant
Static Coefficient of Friction	ASTM C-1028	WET ≥ 0.5 DRY ≥ 0.7
DCOF (WET)	ANSI B101.3	≥ 0.42
This product may contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.		
TVOC Emissions at 14 Days • Low Emitting Material		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.



Product Info:

- Glazed Porcelain Tile
- Matte Finish
- 9mm | 12mm Thicknesses
- Rectified Edge
- PEI Rating = 4
- V3 - Moderate Variation
- Frost Resistance = Yes



www.genrose.com

6"x36" Field Tile in French Oak

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.



www.genrose.com