ZEPHYR









24"x24" Field Tile in Grigio 24"x24" 4 Line | 2 Line Deco in Grigio





24"x24" Field Tile in Bianco





24"x24" Field Tile in Grigio | Nero 24"x24" 2 Line Deco in Greige

AVAILABLE IN:

10mm Field Tiles + Decos

Rectified Edge

48"x48" Matte Finish 24"x48" Matte Finish

36"x36" Matte Finish

24"x24" Matte Finish

12"x24" Matte Finish

Trim Pieces

3"x24" Bullnose Matte Finish

- All sizes are NOMINAL

MADE TO ORDER FIELD TILES AND MOSAICS:

This represents a small portion of the mosaic patterns we offer. We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		2" 4"		1³/ ₈ ″x3″ 2″x4″
		BRICKS		DIAMONDS	
			1"x2" 1"x3" 1 ³ / ₈ "x3" 2"x4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
Half Hexagon	6.7" Base		2"x12"		1"x2" 2"x4" ⁵ / ₈ "x4"
Diamond	4"	0074	CONC	V V V	
Hexagon	6"	OCTAGONS		HEXAGONS	
Chevron	2"x12" 6"x24"		2" w/ 0.6" Squares		1½" 2"
TRAPEZOID W/ DOT		SQUARES		RECTANGLES	
	4"x2 ¹ / ₂ " w/ ⁵ / ₈ " Dot		1"x1" 2"x2" 1 ³ / ₈ "x1 ³ / ₈ " 3"x3"		1"x2" 1"x4"

10mm Field Decos

24"x48" 2 Lines Deco Matte Finish

24"x24" 2 Lines Deco Matte Finish

24"x24" 4 Lines Deco Matte Finish

Rectified Edge







Bianco Grigio





Greige Nero

24"X48" 2 LINES DECO









24"X24" 2 LINES DECO









24"X24" 4 LINES DECO



Bianco







GENROSE



Features	Test Method	Value	
Length and Width	ISO 10545-2	±0.6% / ±2.0mm	
Thickness	ISO 10545-2	±5% / ±0.5mm	
Straightness of Sides	ISO 10545-2	±0.5% / ±1.5mm	
Rectangularity	ISO 10545-2	±0.5% / ±2.0mm	
Surface Flatness	ISO 10545-2	±0.5% / ±2.0mm	
Surface Quality	ISO 10545-2	95% of Tiles with No Defaults	
Water Absorption	ISO 10545-3	≤0.5% Maximum Single Value	
Average Bending Strength	ISO 10545-4	35 N/mm² Min.	
Breaking Strength	ISO 10545-4	≥ 7.5 mm: 1300 N Min. < 7.5 mm: 700 N Min.	
Resistance to Surface Abrasion	ISO 10545-7	4	
Crazing Resistance	ISO 10545-11	Resistant	
Frost Resistance	ISO 10545-12	Resistant	
Chemical Resistance	ISO 10545-13	GB Min	
Stain Resistance	ISO 10545-14	Class 3 Min	
Coeffiecent of Friction	B.C.R.A. Method	Dry: > 0.40 Wet: > 0.40	
Slip Potential	Standards BS 7976-2:2002 Pendulum Tester	Dry: > 63 Wet: > 38	
Antislip Properties	DIN 51130	Matte: R10	
Dynamic Coefficient of Friction	DCOF ANSI A137-1:2012	Wet: > 0.42	

This product will contribute to USGBC registered LEED projects.

It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.

Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Matte Finish
- 10mm Thickness
- Rectified Edge
- PEI Rating = 4
- V2 Slight Shading Variation
- Frost Resistance = Yes



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.



www.genrose.com