

Features	Test Method	Value	
Water Absorption	ISO 10545-3	< 0.5%	
Breaking Strength	ISO 10545-4	> 1300 N	
Bending Strength	ISO 10545-4	> 35 N/mm ²	
Abrasion Resistance	ISO 10545-7	3 - Miel 4 - Gris Blanco Natural	
Cracking Resistance	ISO 10545-11	Resistant	
Frost Resistance	ISO 10545-12	Resistant	
Chemical Resistance	ISO 10545-13	Household	Acid/Alkaline Resistance
		Minimum GB	GHA
Stain Resistance	ISO 10545-14	Resistant	
DCOF (WET)	ANSI A137.1:2012. 9.6	> 0.42	
Hardness (MOHS)	EN 101	Minimum 3	

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Glazed Porcelain Tile
- Matte Finish
- 10mm Thickness
- Rectified Edge
- PEI Rating = 3 - Miel
4 - Gris | Blanco | Natural
- V3 - Moderate Variation
- Frost Resistance = Yes

