



Features	Test Method	Value
Dimensions and Surface Quality	ISO 10545-2	Complies with the Standard
Water Absorption	ISO 10545-3	≤ 0.5%
Breaking Strength	ISO 10545-4	1,600 – 2,400 N
Bending Strength	ISO 10545-4	35 – 45 N/mm ²
Resistance to Deep Abrasion	ISO 10545-6	< 130 mm ²
Thermal Resistance	ISO 10545-9	Resistant
Frost Resistance	ISO 10545-12	Resistant
Chemical Resistance	ISO 10545-13	Class A
Stain Resistance	ISO 10545-14	5
DCOF	-	0.68
Recycled Material	-	≥31%

This product will contribute to USGBC registered LEED projects.
 It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.
 Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Porcelain Tile
- Matte Finish
- 10.5mm Thickness
- Rectified Edge
- V1 - Uniform Appearance
- Frost Resistance = Yes