

Features	Test Method	Value
Dimensions	ISO 10545 - 2	Compliant
Surface Quality		Min. 95% of tiles free of visible defects
Water Absorption	ISO 10545 - 3	0.0295%
Modulus of Rupture / Bending Strength	ISO 10545 - 4	36.04 N/mm ²
Breaking Strength		1,864.7 N
Coefficient of Linear Thermal Expansion	ISO 10545 - 8	2.49 x 10 ⁻⁶
Thermal Shock Resistance	ISO 10545 - 9	Resistant
Crazing Resistance	ISO 10545 - 11	Resistant
Chemical Resistance (Domestic)	ISO 10545 - 13	A
Chemical Resistance (Low Concentration)		LA
Chemical Resistance (High Concentration)		HA
Fire Resistance	-	A1/A1 _{FL}
Slip Resistance	ANSI A326.3	DCOF 0.46
VOC Emissions	-	Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Color Body Porcelain Tile
- Carved Finish
- 8.5mm Thickness
- Rectified Edge
- V2 - Slight Variation
- Frost Resistance = Yes


www.genrose.com