


Features	Test Method	Value
Length and Width	ISO 10545 - 2	± 0.5%
Thickness		± 10%
Straightness of Sides		± 0.3%
Rectangularity		± 0.5%
Surface Flatness		± 0.5%
Surface Quality		Min. 95% of tiles free of visible defects
Water Absorption	ISO 10545 - 3	10% - 20%
Modulus of Rupture / Bending Strength	ISO 10545 - 4	≥ 15N/mm <sup>2</sup>
Thermal Shock Resistance	ISO 10545 - 9	Resistant
Crazing Resistance	ISO 10545 - 11	Resistant
Chemical Resistance (Domestic)	ISO 10545 - 13	≥ B
Chemical Resistance (Low Concentration)		≥ LB
Fire Resistance	-	A1/A1 <sub>FL</sub>
LEED	-	Yes
Recycled Content	-	≥ 17%
VOC Emissions	-	Zero VOC
Environmental Product Declaration	-	Yes



This product will contribute to USGBC registered LEED projects.  
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Ceramic Tile
- Gloss | Satin Finishes
- 7mm Thicknesses
- Pressed Edge
- V1 - Uniform Appearance
- Not Frost Resistant


[www.genrose.com](http://www.genrose.com)