

Features	Test Method	Value
Surface Quality	ISO 10545-2	95% of tiles with no defaults
Length and Width		$\pm 0.6\% \pm 2\text{mm}$
Thickness		$\pm 5\% \pm 0.5\text{mm}$
Straightness of Sides		$\pm 0.5\% \pm 1.5\text{mm}$
Rectangularity		$\pm 0.5\% \pm 2\text{mm}$
Surface Flatness		$\pm 0.5\% \pm 2\text{mm}$
Water Absorption		ISO 10545-3
Bending Strength	ISO 10545-4	35 N/mm <sup>2</sup> min.
Breaking Strength		1300 N min.
Surface Abrasion Resistance	ISO 10545-7	Class 4
Crazing Resistance	ISO 10545-11	Resistant
Frost Resistance	ISO 10545-12	Resistant
Chemical Resistance	ISO 10545-13	Min. GB
Stain Resistance	ISO 10545-14	Min. Class 3
B.C.R.A. D.M. Matte Only	-	Dry: > 0.40 Wet: > 0.40
DIN 51130 Matte Only	-	R9
DCOF (WET) Matte Only	ANSI A137.1	> 0.42
Sustainability	This product will contribute to USGBC LEED v3 and LEED BD&C v4 registered projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700. Low Emissions Material • Zero VOC	

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Color Body Porcelain Tile
- Matte | Polished Finishes
- 10mm Thickness
- Rectified Edge
- PEI Rating = 4 (Matte Finish Only)
- V2 - Slight Shading Variation
- Frost Resistance = Yes

