

Features	Test Method	Value	
Length and Width	ISO-10545-2	± 0.15%	
Admitted Deviation		± 5%	
Maximum Straightness Deviation		± 0.1%	
Maximum Right-angle Deviation		± 0.2%	
Warpage		± 0.35%	
Surface Quality		At least 95% of the tiles must be free from visible flaws	
Water Absorption		ISO-10545-3	0.08%
Breaking Strength	ISO-10545-4	3200 N	
Bending Strength		50 N/mm ²	
Abrasion Resistance	ISO-10545-6	140	
Thermal Shock Resistance		Resistant	
Frost Resistance			
Chemical Resistance	ISO-10545-13	Domestic Chemicals	Low Concentration
		UA	ULA
Stain Resistance	ISO-10545-14	Class 4	
Slip Resistance with Shoes	DIN-51130:2010	Matte	Anti-Slip
		R10	R11
Barefoot Slip Resistance - Anti-Slip Finish	DIN-51097	Class B	
Static Coefficient of Friction	ASTM-C1028	> 0.6 Dry and Wet	
Dynamic Coefficient of Friction	DCOF section 9.6 ANSI A 137.1 2012	> 0.42 wet	
Recycled Material	-	Blanc - 0.7% Noir, Gris, Plombe, Ecreu, Ivoire - 13.8%	
VCOs	-	No Emissions	
 <p>This product is GREENGUARD® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.</p>			

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Matte | Anti-Slip Finish
- 6mm | 10mm Thickness
- Rectified Edge
- V3 - Moderate Variation
- Frost Resistance = Yes



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.