





Features	Test Method	Value	
Dimensions	ASTM C499	Compliant	
Surface Quality		Min. 95% of tiles free of visible defects	
Warpage	ASTM C485	Compliant	
Wedging	ASTM C502	Compliant	
Water Absorption	ASTM C373	≤ 0.5%	
Breaking Strength	ASTM C648	<b>9mm</b>	<b>20mm</b>
		≥ 450 lbf	≥ 2800 lbf
Chemical Resistance (Domestic)	ASTM C650	Conforms	
Recycled Content	-	40%	
Slip Resistance (DCOF)	ANSI A326.3	> 0.42	
LEED	-	Yes	
Environmental Product Declaration	-	Yes	
Greenguard Gold	-	Yes	
Green Squared	-	Yes	
Declare	-	Red List Free	
VOC Emissions	-	Zero VOC	

**Declare.** This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Disclaimer:** DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.



**Product Info:**

- Porcelain Tile
- Matte Finish
- 9mm | 20mm Thicknesses
- Rectified Edge
- V3 - Moderate Variation
- Frost Resistant



[www.genrose.com](http://www.genrose.com)

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.