





Features	Test Method	Value
Thickness	ASTM C499	max ± 0.030 inch
Water Absorption	ASTM C373	≤ 0.5%
Surface Hardness	Mohs Scale	7 Mohs
Bond Strength	ASTM C482 ANSI A 137.1	<sup>3</sup> 50 PSI (0.34 MPa)
Breaking Strength	ASTM C648	450 lbf. avg.
Linear Thermal Expansion	ASTM C372	Conforms
Thermal Shock Resistance	ASTM C484	Conforms
Chemical Resistance	ASTM C650	Conforms
Stain Resistance	ASTM C1378	Conforms
Frost Resistance	ASTM C1026	Resistant
DCOF (WET)	ASTM A326.3 ANSI A 137.1	0.42
Recycled Material	-	40%

This product is GREENGUARD® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700. Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Color Body Porcelain Tile
- Matte Finish
- 9mm Thickness
- Rectified Edge
- Frost Resistance = Yes
- V3 - Moderate Variation
- Application = Residential and Light Commercial



[www.genrose.com](http://www.genrose.com)