

Features	Test Method	Value
Length and Width	ISO 10545-2	± 0.2%
Thickness	ISO 10545-2	± 5%
Warpage of Edges	ISO 10545-2	± 0.2%
Wedging	ISO 10545-2	± 0.2%
Warpage	ISO 10545-2	± 0.2%
Water Absorption	ISO 10545-3	≤0.1%
Modulus of Rupture	ISO 10545-4	50 N/mm ²
Breaking Stress	ISO 10545-4	>1700 N
Coefficient of Linear Thermal Expansion	ISO 10545-8	6.5x10 ⁻⁶ °C ⁻¹
Resistance to Thermal Shock	ISO 10545-9	Resistant
Frost Resistance	ISO 10545-12	Resistant
Chemical Resistance	ISO 10545-13	GB Min.
Stain Resistance	ISO 10545-14	Class 3 Min.
Slip Resistance	DIN51130	Natural - R9 Anti-Slip - R11
Recycled Material	-	>40%
This product contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Natural | Anti-Slip Finishes
- 9mm Thickness
- Rectified Edge
- PEI Rating = 4
- V4 - Substantial Variation
- Frost Resistance = Yes


www.genrose.com