



Features	Test Method	Value	
Water Absorption	ISO 10545-3	≤ 0.5%	
Breaking Strength	ISO 10545-4	1600 -2400 N	
Bending Strength	ISO 10545-4	35 -45 N/mm <sup>2</sup>	
Thermal Resistance	ISO 10545-9	Resists	
Crazing Resistance	ISO 10545-11	Resists	
Frost Resistance	ISO 10545-12	Resistant	
Chemical Resistance	ISO 10545-13	Household Chemical	Low Concentration
		A	B
Stain Resistance	ISO 10545-14	5	
Recycled Material	-	31%	
  <p style="text-align: center;">This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700. Low Emissions Material • Zero VOC</p>			

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Glazed Porcelain Tile
- Polished Finish
- 10.5mm Thickness
- PEI Rating = 2 (Nacar | Seagreen) | 4 (White)
- V3 - Moderate Variation
- Frost Resistance = Yes



[www.genrose.com](http://www.genrose.com)