

Features	Test Method	Value	
Length and Width	ISO 10545-2	± 0.6%	
Thickness		± 5%	
Wedging		± 0.6%	
Warpage		± 0.5%	
Water Absorption	ISO 10545-3	≤ 0.5%	
Bending Strength	ISO 10545-3	R ≥ 35 N/mm ²	
Deep Abrasion Resistance	ISO 10545-7	Matte	Polished
		Bianco: IV	Bianco: IV
		Grigio: IV	Grigio: IV
		Blu: IV	Blu: III
		Nero: III	Nero: II
Coefficient of Linear Thermal Expansion	ISO 10545-8	Matte	Polished
		9x10-5x C-1	9x10-5x C-1
Resistance to Thermal Shock	ISO 10545-9	Resistant	
Crazing Resistance	ISO 10545-11	Resistant	
Frost Resistance	ISO 10545-12	Resistant	
Chemical Resistance	ISO 10545-13	Resistant	
Stain Resistance	ISO 10545-14	min. Class 3	
DCOF (WET)	BOT 3000	≥ 0.60	
Breaking Load	EN 14411:2016	≥ 1300 N	
Bond Strength		1 N/mm ²	
Thermal Shock Resistance		Resistant	
Fire Resistance		A1fl/A1	

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Matte | Polished Finish
- 9mm Thickness
- Rectified | Pressed Edge
- V3 - Moderate Variation
- Frost Resistance = Yes

