

Features	Test Methods	Value
Water Absorption	ASTM C373	≤ 0.1%
Bond Strength	ASTM C482	≥ 200 psi
Warpage Average Edge	ASTM C485	≤ ± 0.40%
Warpage Average Diagonal		≤ ± 0.40%
Range of Thickness	ASTM C499	≤ ± 0.04 Inc.
Average Facial Dimension		≤ ± 0.25%
Wedging	ASTM C502	≤ ± 0.25%
Breaking Strength	ASTM C648	≥ 400 lbf
Chemical Resistance	ASTM C650	Class A
Frost Resistance	ASTM C1026	No evidence of damage
Visible Abrasion Resistance	ASTM C1027	Class 4
Stain Resistance	ASTM C1378	Class A
Coefficient of Friction (DCOF)	BOT 3000	≥ 0.55*
Hardness (MOHS)	Scratch Test (No regulated)	≥ 7
Aesthetic Classification	Visual Evaluation Shade & Texture	V2
Thermal Shock Resistance	-	Guaranteed
VOCs	-	No Emissions
		This product is GREENGUARD® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Color Body Porcelain Tile
- Honed | Polished Finish
- 8mm Thicknesses
- Rectified Ed
- PEI Rating = 4
- V2 - Slight Shading Variation
- Frost Resistance = Yes



[www.genrose.com](http://www.genrose.com)