





Features	Test Method	Value	
Dimensions	ISO 10545 - 2	Compliant	
Surface Quality		Min. 95% of tiles free of visible defects	
Water Absorption	ISO 10545 - 3	≤ 0.1%	
Modulus of Rupture / Bending Strength	ISO 10545 - 4	55.2 N/mm <sup>2</sup>	
Breaking Strength		<b>9mm</b>	<b>20mm</b>
		2436 N	> 10000 N
Deep Abrasion Resistance	ISO 10545 - 6	149 mm <sup>3</sup>	
Coefficient of Linear Thermal Expansion	ISO 10545 - 8	~ 7 (10 <sup>-6</sup> °C <sup>-1</sup> )	
Thermal Shock Resistance	ISO 10545 - 9	Resistant	
Crazing Resistance	ISO 10545 - 11	Resistant	
Chemical Resistance (Domestic)	ISO 10545 - 13	A	
Chemical Resistance (Low Concentration)		LA	
Chemical Resistance (High Concentration)		HA	
Fire Resistance	-	A1/A1 <sub>FL</sub>	
Slip Resistance (Wet)	ANSI A326.3	<b>Matte</b>	<b>Anti-Slip</b>
		DCOF 0.76	DCOF 0.89
Environment Product Declaration	-	Product Specific	
Health Product Declaration	-	Available	
Declared	-	Red List Free	
Recycled Content	-	<b>Pavers</b>	
		20%	
LEED	-	Yes	
VOC Emissions	-	Zero VOC	

This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Disclaimer:** DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

**Product Info:**

- Porcelain Tile
- Rectified Edge
- Matte | Anti-Slip Finishes
- V2 - Slight Variation
- 6mm | 9mm | 20mm Thicknesses
- Frost Resistant

