

Features	Test Method	Value
Thickness	C499	Range: 0.04 in
Warpage (edge)	C485	Warpage $\pm$ 0.4% or $\pm$ 0.05 in
Warpage (diagonal)		Warpage $\pm$ 0.4% or $\pm$ 0.07 in
Wedging	C502	$\pm$ 0.25% or $\pm$ 0.03
Water Absorption	C373	$\leq$ 0.5%
Breaking Strength	C648	250 lbf or Greater
Resistance to Thermal Shock	C484	Resistant
Resistance to Freeze / Thaw Cycling	C1026	
Chemical Resistance	C650	
Resistance to Stain	C1378	
DCOF Average Dynamic Coefficient of Friction	BOT 3000 Test	$\geq$ 0.42




This product will contribute to USGBC registered LEED projects.  
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.  
Low Emissions Material • Zero VOC



According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Color Body Porcelain Tile
- Matte Finish
- 9mm Thickness
- Rectified Edge
- V2 - Slight Shading Variation
- Frost Resistance = Yes



[www.genrose.com](http://www.genrose.com)