

Features	Test Method	Value
Dimensions	ASTM C499	Compliant
Surface Quality		Min. 95% of tiles free of visible defects
Warpage	ASTM C485	Compliant
Wedging	ASTM C485	Compliant
Water Absorption	ASTM C373	≤ 0.5 %
Breaking Strength	ASTM C648	≥ 2500 lbf
Recycled Material	-	≥ 40%
Slip Resistance (Wet)	ANSI A137.1	DCOF 0.49
Environmental Product Declaration	-	Yes
Health Product Declaration	-	Yes
Greenguard Gold	-	Yes
Green Squared	-	Yes
Declare	-	Red List Free
VOC Emissions	-	Zero VOC







This product will contribute to USGBC registered LEED projects.
 It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Product Info:

- Color Body Porcelain Tile
- Natural Finish
- 10mm | 20mm Thicknesses
- Rectified Edge
- V2 - Slight Variation
- Frost Resistant



www.genrose.com