

Features	Test Method	Value
Water Absorption	ASTM C373	≤0.1%
Bond Strength	ASTM C482	≥ 200 psi
Warpage Average Diagonal	ASTM C485	≤ ± 0.40%
Warpage Average Edge		≤ ± 0.40%
Thickness Dimension	ASTM C499	≤±0.04 Inc.
Facial Dimension		≤ ± 0.25%
Wedging	ASTM C502	≤ ± 0.25%
Breaking Strength	ASTM C648	≥ 400 lb.
Chemical Resistance	ASTM C650	Class A
Frost Resistance	ASTM C1026	Resistant
Visible Abrasion Resistance for Glazed Tiles	ASTM C1027	Class 4
Stain Resistance	ASTM C1378	Class A*
DCOF-Honed	BOT 3000	≥0.50
DCOF-Textured		≥0.65
Hardness (Mohs)	Scratch Test (No regulated)	≥ 7
Aesthetic Classification	Visual Evaluation Shade & Texture	V2
 <p>This product is GREENGUARD® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.</p>		

\*All values given are for matte or honed material. No values are given for polished material. GENROSE does not recommend polished surfaces in areas subject to exposure from grease, oil or water.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide.

**Product Info:**

- Color Body Porcelain Tile
- Honed | Anti-Slip Finish
- 7.5mm (Cove Base) | 8mm Thickness
- Rectified Edge
- PEI Rating = 4
- V2 - Slight Shading Variation
- Frost Resistance = Yes



[www.genrose.com](http://www.genrose.com)