



Features	Test Method	Value				
		Matte	Glazed	Anti-Slip		
Size	ISO 10545-2	Comply				
Water Absorption	ISO 10545-3	≤ 0.1%	Comply	≤ 0.1%		
Bending Strength	ISO 10545-4	Comply	Comply	≥ 3000 N		
Breaking Strength	ISO 10545-4	-	-	> 10,000 N		
Impact Resistance	ISO 10545-5	≥ 0,80	≥ 0,80	-		
Resistance to Deep Abrasion	ISO 10545-6	<145 mm <sup>3</sup>	-	<145 mm <sup>3</sup>		
Thermal Linear Expansion Coefficient	ISO 10545-8	≈7 (10-6 °C <sup>-1</sup> )	≈7 (10-6 °C <sup>-1</sup> )	≈7 (10-6 °C <sup>-1</sup> )		
Thermal Shock Resistance	ISO 10545-9	Resistant	Resistant	Resistant		
Expansion in Humidity	ISO 10545-10	Comply	Comply	≤ 0.1 (mm/m)		
Crazing Resistance	ISO 10545-11	-	Comply	-		
Frost Resistance	ISO 10545-12	Resistant	Resistant	Resistant		
Resistance of Chemical Attack	ISO 10545-13	Resistant	Resistant	Resistant		
Resistance to Stains	ISO 10545-14	Cleanable	Cleanable	Cleanable		
Static Load	EN 12825	-	-	Center Center Side Diagonal		
Breaking Load Class	EN 1339	-	-	U11 T11		
Slip Resistance	DCOF	Comply	-	Comply		
Nominal Thickness		63"x126" 63"x63"	6mm	3"x12"	8.5mm	20mm
		48"x48" 24"x48" 24"x24" 12"x24"	9mm			