



Features	Test Method	Value
Length and Width	ISO 10545 - 2	±0.9mm
Thickness		±0.5mm
Straightness of Sides		±0.75mm
Rectangularity		±0.75mm
Surface Quality		Min. 95% of tiles free of visible defects
Water Absorption	ISO 10545 - 3	≤ 0.2%
Modulus of Rupture / Bending Strength	ISO 10545 - 4	≥ 45 N/mm ²
Breaking Strength		≥ 1300 N
Coefficient of Linear Thermal Expansion	ISO 10545 - 8	$\alpha \leq 7.1 \times 10^{-6} \text{ }^{\circ}\text{C}^{-1}$
Thermal Shock Resistance	ISO 10545 - 9	Resistant
Crazing Resistance	ISO 10545 - 11	Resistant
Chemical Resistance (Domestic)	ISO 10545 - 13	A
Chemical Resistance (Low Concentration)		LA
Chemical Resistance (High Concentration)		HA
Fire Resistance	-	A1/A1 _{FL}
Slip Resistance (Wet)	ANSI A326.3	DCOF Does Not Pass
LEED	-	Yes
Recycled Content	-	≥ 50%
VOC Emissions	-	Zero VOC
Environmental Product Declaration	-	Yes



This product will contribute to USGBC registered LEED projects.
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Glazed Porcelain Tile
- Polished Finish
- 9.5mm Thickness
- Pressed Edge
- Frost Resistant
- PEI Rating by Color:
 - 5 - White
 - 4 - Light Grey
 - 3 - All Other Colors
- V1 - Uniform Appearance - White
- V3 - Moderate Shading Variation - All Other Colors



www.genrose.com